


Technical Report
Number 102



Social and Economic
Studies Program

Sponsor:
Minerals Management
Service

Alaska Outer
Continental
Shelf Region

North Aleutian Basin Transportation Methodology

•

•

•

•

•

•

•

•

•

TECHNICAL REPORT 102

CONTRACT NO. 14-12-0001-30011

SOCIAL AND ECONOMIC STUDIES PROGRAM
ALASKA OCS REGION

NORTH ALEUTIAN BASIN TRANSPORTATION METHODOLOGY

Prepared for

MINERALS MANAGEMENT SERVICE.
ALASKA OUTER CONTINENTAL SHELF REGION
Anchorage, Alaska

Prepared By

ERE SYSTEMS, LTD.
Arlington, Virginia

November 1984

NOTICE

This document is disseminated **under** the sponsorship of the **U.S.** Department of Interior, Minerals Management Service, Alaska Outer Continental **Shelf** Region, in the interest of information exchange; The **U.S.** Government assumes no liability for its content or use thereof.

Social and Economic Studies Program
Alaska OCS Region

NORTH ALEUTIAN BASIN TRANSPORTATION METHODOLOGY

Prepared **By:**
ERE SYSTEMS, LTD.
Arlington, Virginia

Table of Contents

	<u>PAGE</u>
LIST OF TABLES	vii
LIST OF FIGURES	ix
ABSTRACT	xi
I. INTRODUCTION	1
Overview of the Methodology	3
Population, Employment and the Economy	8
Commercial Fishing	10
Petroleum Development Base Case	11
Petroleum Development OCS Case	17
II. MARINE TRANSPORTATION	21
MARINE TONNAGE DEMANDS	23
Base Case	25
Unalaska/Dutch Harbor	26
Outbound Tonnage	26
Inbound Tonnage	43
Cold Bay	46
St. George Island	47
St. Matthew Island	48
Aleutian Transshipment Terminal	50
OCS Case	51
Unalaska/Dutch Harbor	52
Cold Bay	53
St. George Island	53
St. Matthew Island	53
Aleutian Transshipment Terminal	54
MARINE VESSEL REQUIREMENTS	54
Base Case	57
Unalaska/Dutch Harbor	57
Cold Bay	65
St. George Island	65
St. Matthew Island	66
Aleutian Transshipment Terminal	67
OCS Case - Equipment And Supplies	67
Work Boat and Tug Boat Trip Making	68
Rig and Platform Support	68
Pipeline Support	71
Tanker Support	71
Other Vessel Traffic	73
OCS Case - Resource Movements	73

111.	AIR TRANSPORTATION	75
	Non-OCS Related Transportation Demands	76
	Defining the System	76
	Air Travel Demands	79
	Aircraft Operations	81
	Scheduled Commercial Operations	82
	Other Operations	85
	OCS Related Transportation Demands	87
	REFERENCES	93

List of Tables

Table	Title	Page
1	Drilling Materials Requirements - 15,000 Foot Well	39
2	Examples Of The Range Of Vessel Capacities	56
3	Assumed Number Of Marine Vessels For Specific OCS Activities	58
4	Typical Monthly Supply Boat Movements	70

VIII

List of Figures

Figure	Title	Page
1	Illustrated Variations in Transportation - Demands For Different Economic Conditions	5
2	OCS Lease Sale Planning Areas	13
3	General Formula For Throughput Marine Tonnage	24
4	Formula For Base Case Outbound Marine Tonnage at Unalaska/Dutch Harbor	27
5	Formula For Base Case Inbound Marine Tonnage at Unalaska/Dutch Harbor	44
6	General Formula For Determining Vessel Round Trips	55

7

11

11

1

.

●

●

●

●

ABSTRACT

NORTH ALEUTIAN BASIN TRANSPORTATION METHODOLOGY

The principal objective of this report is to develop for the Minerals Management Service (MMS), Alaska Outer Continental Shelf (OCS) Region, a methodology to evaluate potential changes in transportation services affected by possible development of the North Aleutian Basin. The need for this methodology is driven by a proposed April 1985 lease sale in this offshore basin. In preparing for this sale, MMS is evaluating the effects of this potential development on **social** and economic activities in the surrounding area. Due to the remote character of this area, marine and air transportation services are an important economic activity potentially affected by the logistical requirements of the petroleum industry. The methodology consists of a set of forecasting and analysis procedures with associated **assumptions** about expected future events or activities, plus recommended standards for certain predetermined conditions.

The methodology seeks to define and evaluate, for each transportation mode, the incremental difference between conditions likely to occur without the North Aleutian lease sale and conditions **likely** to occur with the lease sale. The differences between these two sets of conditions for some horizon year are presumed to be indicators of the affects of the lease offering. In an application of this methodology, these indicators are further evaluated to determine the nature of expected changes.

In developing each set of conditions, the methodology seeks to establish a basis for economic change in the Aleutian Islands. Although the

economy is evaluated in detail by other contractors, several assumptions are made about future economic development in the **Aleutians**, including expected petroleum development activities. The resultant economic description provides the basis for procedures to forecast and evaluate future transportation demands. **In** subsequent steps, explained in **detail** in the text, these demands are converted to operational characteristics (aircraft or marine **vessel** activities). In the application **of** this methodology, these operational characteristics would be compared to the operational capacity of existing and future facilities (information developed in previous studies), in order **to** determine possible deficiencies.

The North Aleutian **lease** sale presents a unique set of circumstances with regard to this methodology because three other offshore lease sales have been held in the geographically proximate area. The three prior **sales** were held in the Norton Basin during November **1982**; in the **St. George** Basin during February **1983**; and in the **Navarin** Basin during **April 1984**. The methodology must consider the influence of these prior **sales** on future conditions without the North Aleutian sale.

The suggested methodology is largely based on information available through existing secondary and some primary sources. Over time, **the** sources will grow out of date and be replaced by newer, hopefully better, information. As the quality of the data changes, so to the methodology. The consequence of this relationship **is** that the methodology may have a time **value** similar to that of the data supporting it. **The** time value of this supporting data should be kept in mind when this document is subsequently used.

INTRODUCTION

The **principal** objective of this report is to develop for the Minerals Management Service (MMS) a methodology to forecast and evaluate future changes in marine and air transportation services potentially affected by development of **the** North Aleutian Basin. The methodology consists of a set of procedures with associated assumptions **about** expected future events or activities and recommended standards for certain predetermined conditions. The MMS intends to use this methodology to evaluate transportation demands generated from a proposed April 1985 offshore lease offering in the North Aleutian Basin. The methodology is expected to **be** applied by various MMS staff, whose formal education, for the most part, is in areas other than transportation planning. Thus, a second objective of this report is to make the methodology as clearly understood and widely usable as possible.

It should be noted that certain assumptions used in this document are based on incomplete knowledge of expected economic and petroleum development activities. In the context of the Social and Economic Studies Program, economic data is typically contained in documents produced by other contractors or by MMS itself, while petroleum development data is produced solely by MMS. Certain aspects of the

methodology also **deal** with cumulative conditions imposed **by** prior **lease sales**. Information about prior sales is typically stipulated **by** MMS, either directly or by incorporation **of** related assumptions and other data in the Man in the Arctic Program (MAP) Econometric Model, run by a Social and Economic Studies Program contractor. **At** the time **this report** was prepared, neither the economic data nor proposed petroleum development information was complete. Nonetheless, certain assumptions were made **to replace** this missing information. **As** knowledge of these activities improves, the various assumptions need **to be** reviewed and changed, **as** necessary.

One final point needs to **be** made in introducing this document. **The methods** suggested and employed herein are for **the most** part based on information available through existing secondary and some primary sources. Over time, the sources grow out **of** date and the data are no **longer** applicable, being replaced by newer, hopefully better, information. As the quality of the data changes, so to the methodology. The consequence of this relationship is that the methodology may have a time **value** similar to that of the data supporting it. The time **value of** this supporting data should be kept in mind when **this** document is subsequently used.

OVERVIEW OF THE METHODOLOGY

The methodology seeks to define and evaluate, for each transportation mode, **the** incremental difference between conditions likely to occur without the specific lease offering (hereinafter referred to as the Base Case) and conditions likely to occur with the specific lease offering (hereinafter referred to as the **OCS** Case). Forecast conditions include numerical estimates of transportation demand requirements and supply capacity. The numerical differences between Base Case and OCS Case conditions for some horizon year are presumed to be indicators of the affects of the lease offering. In the application of this methodology, these indicators are further evaluated to determine if the expected change has a **positive,or** negative effect on use of the transportation system by today's societies.


The portion of the methodology presented in this report deals **with** development of the Base Case and OCS Case conditions and their numerical representation. In developing each case, the methodology seeks **to** establish a basis for economic change and, from this base, forecast relevant transportation demands. **In** turn, the transportation demands are converted to operational characteristics (aircraft or marine vessel activities). Transportation capacity and expected changes in transportation supply are assessed separately. Transportation capacity and supply information relevant to the North Aleutian Basin can be found

in the following Social and Economic Studies Program reports: Technical Report 52 (Peat, Marwick, Mitchell & Co. and J. Lindsay & Assoc., 1980); Technical Report 58 (Peat, Marwick, Mitchell & Co. and ERE Systems, Ltd., 1981); Technical Report 66 (ERE Systems, Ltd., 1982); and Technical Report 84 (Louis Berger and Associates, Inc., 1983). In the final step, a comparative analysis between demand and supply is made to determine whether the existing facilities and services can continue to function at acceptable levels.

The North Aleutian lease offering presents a unique set of circumstances with regard to this methodology because three other offshore lease sales have been held in the geographically proximate area prior to the North Aleutian lease offering. The situation can best be visualized in Figure 1, which shows variations in transportation demand over time for various conditions. The bottom line (curve "A") represents both a historic demand curve and a set of future demand conditions that might exist if there was no OCS development in the region. That is, changes in economic conditions, and therefore, transportation demand, would be due to factors other than oil and gas development. In the Aleutian region, commercial fishing, and particularly fishing for underutilized species, could provide the impetus for such non-OCS economic growth.

The middle curve in Figure 1, curve "B", represents a set of conditions that might exist when economic activities related to the three prior

FIGURE 1
 ILLUSTRATED VARIATIONS IN TRANSPORTATION DEMANDS
 FOR DIFFERENT ECONOMIC CONDITIONS



SOURCE: ERE Systems, Ltd.

lease offerings are added to conditions represented by curve "A". Soon after each lease sale, petroleum development activity begins and the added transportation demands rise and fall in response to these new economic stimulants. The vertical difference between the bottom curve "A" and the middle curve "B" is the increase in transportation demand due to the three lease offerings.

The top curve in Figure 1, curve "C", represents conditions that might exist if, in addition to the three earlier lease offerings, a fourth lease sale was held at a later date. In the context of this analysis, the fourth sale is the North Aleutian Basin. As a result of this additional lease offering, there is an incremental increase in economic activity and, as shown by the vertical difference between the curves "B" and "C", there is also an incremental increase in transportation demand. The methodology described in this document seeks to develop the middle and top forecast curves for each transportation mode in order to measure the incremental change in transportation demand due to only the latest lease offering. By converting the various economic and petroleum development demands into operational characteristics, the effects on cargo handling capabilities, facility capacity, and quality of service can be evaluated.

One of the most important external components to this methodology is the economy and its related demographic characteristics, both of which drive

- transportation demand. The economy is external to this methodology only because the economic analyses and forecasts are conducted by other contractors. Normally, the economy would be considered an integral part of a transportation demand study. In the context of this methodology, changes to the local and regional economy are of primary interest, since **local** community and region-serving transportation facilities are most directly affected by **OCS** activities. To adequately assess the affects of OCS transportation demands, the economic aspects of proposed OCS development must be translated into **local** and regional economic changes. In developing the OCS Case forecast, these OCS imposed economic changes must **be juxtapositioned** with economic changes expected to occur normally.

•

Within the general organization of this report, these economic factors are presented first, to the extent they are known or can be assumed. In succession after the economic discussion are presented each of the other components of the methodology, organized by transportation mode. Only the marine and aviation transportation systems are addressed since these are the only regional systems in the North Aleutian Basin. The specific formulas used to develop transportation demands and to convert demands to operational requirements are discussed for each mode.

•

POPULATION. EMPLOYMENT AND THE ECONOMY

Economic conditions are a **major factor in determining** demand levels for any transportation mode. **In** air transportation, for example, **higher** levels of air passenger **travel** demands can be correlated **with** a rise in household or personal income. Similarly, when businesses are operating **in** a rising economic cycle, business **travel** demands and goods shipments also **rise**. This section explores development of **the** economic information that drives changes **in** transportation demand.

Among a variety of methods, transportation demand can be defined **in** terms of **per capita** consumption rates (**e.g.** air trips or marine tonnage **per capita**), **or** in **terms** of commercial or industrial growth expectations (**e.g.** a doubling of commercial fishing operations can be assumed **to double** existing transportation demands, **all other** factors being **equal**). **In** the context of this methodology, the focus of the economic analysis is **twofold: 1)** to find within historic economic data and historic transportation demand information, the per capita or growth linkages between economic conditions and transportation demand; and 2) **to** identify forecast population and commercial or industrial growth trends to which the historic per capita or growth relationships can be applied **to derive future** transportation demand. **The** historic **per** capita or **growth** linkages are typically developed as part of the research related to defining existing transportation facilities and services (**see**

relevant portions of the various Technical Reports cited earlier).

● For the purpose of preparing this methodology, it is assumed MMS will be deriving population, employment, and economic data from either **local** community studies or through the MAP econometric model. This **latter model** is operated **by** the University of Alaska, Institute for **Social** and Economic Research (**ISER**). The model can provide forecasts of expected economic conditions in the State as a whole and in its various major subregions, and has the capability to feed economic data to a separate community **level model**. In conjunction with MMS, **ISER** has developed a detailed set of assumptions about how major economic trends and construction projects of statewide significance (such as **oil** and gas facilities) **will** be incorporated into the **model**. These various . assumptions are incorporated herein by reference (see University of Alaska, Institute for Social and Economic Research, **1981**). Researchers using the methodology in this report **should** check for consistency between the assumptions made-herein and those employed in producing the latest output from the MAP model.

In the **MAP** model, two economic scenarios are developed to represent growth in the economy: one scenario excludes activities expected from the proposed lease offering (i.e. conditions without the offering or "base case"); the second includes these activities (i.e. conditions with the offering or "OCS case"). The Base Case economic scenario normally

includes all relevant statewide and regional economic changes that are reasonably expected to occur in the future. For example, construction of the Northwest Gas Pipeline or the **Susitna Dam**. Development of the commercial fishing industry in the southern Bering **Sea and** the cumulative effects of the three preceding offshore **lease** offerings are of particular regional interest to the economic Base Case **for** the North Aleutian Basin lease **sale**.

COMMERCIAL FISHING

In the past, there has **been** considerable debate **about the** magnitude of **the** fishing activities that **might** evolve as a **result** of exploitation of underutilized fish species (**groundfish**). **In** prior studies **conducted** for the State and for the Social and Economic **Studies** Program, fishing **has** been identified as the major part of the present and **future** economy **of** the region (see **Earl R. Combs, Inc, 1981**; and Terry, **J.M., Stoles, R.G. & Larson, D.M., 1980**). One of the major problems in forecasting the Base Case is accurately measuring the expected direction of the **groundfishing** industry. Previous forecasts have covered a broad range of expectations. Of considerable importance to this methodology are the assumptions about how the fishing industry will attract employment. Specifically, assumptions pertaining to the magnitude of transient fishing industry employment and assumptions about the rate of change from transient to locally based fishing employment can be expected to

influence air transportation demands directly and marine transportation demands indirectly.

Prior studies have assumed that a **large** percentage **of groundfish** industry employment will initially come from other parts of **Alaska** and from outside Alaska (Terry, J.M., Stoles, R.G., & Larson, D.M., 1980). Presently, most traditional species workers are transient and tend to stay for most of the fishing season. However, the seasons **last only** several months: Salmon set **gillnets** - 2 months; **Salmon** drift **gillnets** and purse seines - **3** months; and crab - **7** months (Earl R. Combs, Inc, 1981). **In** contrast, the groundfishing industry has no season, per se. **If** the **groundfish** workers are transient, based on some periodic rotation to their normal homes, this implies an increased demand on aviation services. As the industry grows and the **workforce** transitions to a higher percentage of **local** employment due to in-migration, workers **travel** less, but many may bring families, thereby increasing demands on both air and marine transportation services-in a different way.


PETROLEUM DEVELOPMENT - BASE CASE

Another economic issue is the affect of cumulative prior lease offerings. These **also** have specific relevance to this methodology and are discussed in the following paragraphs. The North Aleutian Lease Sale is the fourth in a succession of four offshore basins offered for

lease in **the** Bering Sea. Within the Base Case economic scenario, the three lease offerings that **precede** the North Aleutian offering are assumed to stimulate the population and economy of **the** region at **the** same time fishing activities **are** accelerating. **Within** the framework of **this** methodology the assumed cumulative characteristics of these prior OCS offerings become a part of **the** Base Case transportation demand forecast.

The three prior lease offerings are in the Norton Basin, St. George Basin, and Navarin Basin. See Figure 2 for locations. The Norton Basin lease sale was held during November 1982; the St. George lease sale was held in February 1983; and the Navarin Basin lease sale was held in April 1984. The number of possible combinations of events from these three prior sales is impossible to forecast within the framework of this methodology. Consequently, some surrogate condition(s) must be assumed for each lease area in order to provide a representative interpretation of these events. Assuming a high level of activity for the prior sales would submerge the North Aleutian impacts, while assuming a low level of activity would make the North Aleutian events to be of greater significance then may be warranted.

It is assumed that, at a minimum, exploration activities will occur in each of these lease offering areas. Since a marine support base has already been developed at Unalaska/Dutch Harbor (Tremont, J., 1983), it



is assumed this base will be used to directly support the marine transportation demands for the St. George Basin. If a **small marine** support base is established on St. Matthew Island to serve **Navarin Basin** exploration, **Unalaska/Dutch Harbor will likely** serve as the **principal** staging area (**Louis Berger & Associates, Inc., 1983**). Existing facilities at Nome are assumed to directly support the marine transportation demands related to the Norton Basin, with some indirect support provided at **Unalaska/Dutch Harbor**.

With regard to aviation support during exploration activities, the airport at Cold Bay is expected to serve as the principal - staging facility. Although **Unalaska/Dutch Harbor** provides a better coordinated location, the airport runway has not been lengthened, and may not be without massive state aid (**Dames & Moore, 1980b**). However, the runway on **St. George Island** recently has been lengthened by 1,000 feet. (**Tremont, J., 1983**), and offers alternative or emergency aviation access to the **St. George Basin** and **Navarin Basin** offshore areas. A gravel airstrip on St. Matthew Island, which was assumed in conjunction with the support base in the **Navarin Basin** studies, (see **Louis Berger & Associates, Inc., 1983**), could provide more direct air support in the **Navarin Basin**, eliminating the need to use the **St. George runway** except in emergencies. However, a runway on St. Matthew Island might do considerable environmental damage and, as a result, become such a political or judicial issue that it is never constructed. In summary,

exploration related air transportation support to offshore locations in the **St. George** and **Navarin** Basins is expected to be centered at Cold **Bay**, with alternative support to the St. George Basin provided at St. George **Island** and alternative support to the **Navarin** Basin provided at **St. Matthew Island**.

All exploration related air support to the Norton Basin is expected to be handled through Nome with no secondary support from Aleutian **bases**.

In Technical Report 80, Dames & Moore assumed it unlikely that three, much **less** than four, of the basins would reach the development stage (Dames & Moore and Harrison, G. S., **1982**). The probability of such development **occurring** concurrently was considered more remote. **However**, for purposes of presenting this **methodology we** have assumed each of these three basins are developed in accordance with the somewhat concurrent schedule suggested in **Table 2-1** of Technical Report **80**.

One of the primary facilities supporting the transportation of petroleum products from **all** four **lease sale** areas is a Very Large Crude Carrier (**VLCC**) terminal located **in** the Aleutians and hereinafter referred to **as** the Aleutian Transshipment Terminal. The general concept is that shuttle tankers or pipelines would bring the crude petroleum products from the lease sale areas to the terminal and **VLCC** ships would move the products to market (see several versions of this concept: Dames & Moore,

1980a; Dames & Moore and Harrison, G. S., 1982). The location of this terminal has not been determined, although two sites have potential for the harbor, airport, and infrastructure requirements: Unalaska Bay (Unalaska/Dutch Harbor) and Cold Bay/Morzhovoi Bay. Due to poor airport facilities and potential harbor congestion, Unalaska/Dutch Harbor is somewhat less favorable than Cold Bay/Morzhovoi Bay (Dames & Moore and Harrison, G. S., 1982).

During the development stage, it is assumed a small marine support base is developed on St. Matthew Island to serve rigs and platforms in the Navarin Basin (Louis Berger & Associates, Inc., 1983). Primary marine support for this forward base would come from Unalaska/Dutch Harbor, or a new base at Morzhovoi Bay operated in conjunction with the Aleutian Transshipment Terminal. Subsequently, during the production stage, Navarin Basin resources are moved by shuttle tankers operating between a loading terminal on St. Matthew Island and the Aleutian Transshipment Terminal (Dames & Moore and Harrison, G.S., 1982). In the St. George Basin, a pipeline is assumed to bring crude oil products from the lease area to the Aleutian Transshipment Terminal. In the Norton Basin, ice strengthened shuttle tankers operating from offshore loading platforms in Norton Sound are assumed to move products to the Aleutian Transshipment Terminal (Dames & Moore and Harrison, G.S., 1982).

PETROLEUM DEVELOPMENT - OCS CASE

In the OCS Case, as defined earlier, the activities of the **North Aleutian** Lease Sale are added to those described above for the Base Case. The timing of North Aleutian exploration activities generally coincides with the beginning of the development stage in the Norton Basin, and mid point of exploration in the **St. George** and **Navarin** Basins. The scenarios used by Dames & Moore in Technical **Report 80** (Dames & Moore and **Harrison, G.S., 1982**) assume that a petroleum discovery has been made in the St. George and Navarin basins and that continuing exploration activities are focused on delineation of the fields. Before a decision is made to develop either the St. George or **Navarin** Basins, the scenario for the North Aleutian area assumes a discovery is made there too. Thus, before any major development decisions are made, the knowledge about the likely size of the respective finds is assumed to be known. The approximate timeframe to reach this point is **late 1987** or early 1988.

With respect to marine support operations, **one of** the more difficult questions is likely **to** be the continued use of **Unalaska/Dutch** Harbor as the principal marine support base. In the **Navarin** Basin analysis, the combination of the **Navarin** and St. George development activities at **Unalaska/Dutch** Harbor were forecast to most likely exceed the present capacity of the port by 1992 (Louis Berger & Associates, Inc., 1983).

Due to fluctuating OCS demands, **this** condition **would last** only **about three or four years** but resurface by 2000. Improved operational procedures **with** regard to the handling **of** refined petroleum products would improve the situation, **but** may not be feasible without cooperation from the various dock owners. The possible addition of North Aleutian exploration activities in 1986 raises cargo throughput levels, **but** is not expected to seriously effect port capacity. However, the addition **of** North Aleutian development activities, even with the operational improvements, may or may not exceed capacity.

For purposes of **beginning** the analysis, **it will** be assumed that North Aleutian marine activities during the exploration stage are located at **Unalaska/Dutch** Harbor. During the development **stage**, however, marine activities are shifted to a location nearby the Aleutian Transshipment Terminal. This support base is assumed to **be** supplied directly from the Lower **48**, **as well** as through **Unalaska/Dutch** Harbor. The base **also** is assumed to serve **as** an **auxiliary** base for the St. George Basin when operations at **Unalaska/Dutch** Harbor can no **longer** be efficiently conducted - specifically, between 1992 and **1995**, and after 2000 (Louis **Berger** and Associates, **Inc.**, 1983). **In** the application of this methodology, this hypothesis and its **timing** must be examined through sensitivity testing, particularly in **light** of the **assumption** that **all** four **lease** areas will be developed. Subsequent applications of the methodology might well begin with different assumptions regarding other

lease sales activities **vis-a-vis** North Aleutian activities.

No major improvements to existing aviation facilities are assumed - specifically **at Unalaska/Dutch** Harbor. Consequently, aviation support to the **St. George** and **Navarin** Basins is assumed to follow the same pattern as described earlier with primary staging **occurring** at Cold Bay. The new support base at **Morzhovoi** Bay (Aleutian Transshipment Terminal) **will** require a new airfield. Primary staging, however, is assumed to continue at Cold Bay.

Assumptions associated with the fishing issue and those related to prior **lease** offerings are economic factors and, as such, constitute inputs to **ISER's** MAP Model. For this reason they **fall** outside this methodology. However, the assumptions made for the MAP Model also become important inputs to this methodology, as noted in the discussion above. Other important outputs of the MAP modeling effort are the various population forecasts produced by the model itself. Of particular interest in this transportation study are forecasts for the Municipality of Anchorage, the Wade Hampton Census Division, and Census Divisions encompassing the following areas or regional centers: Aleutian Islands, North Slope Borough, Bethel, and Nome. The specific use of these various forecasts is explained further in later sections of this methodology. It is assumed that **ISER**, through its use of the MAP model, will develop Base Case and OCS Case population forecasts for these Census Areas. In the

absence of regional population data from the MAP model, some proportional adjustment can be made to available **1980 Census** data, or future population estimates can be extrapolated from historic trends and net natural increase (birth/death) statistics. Such information is available from the Alaska **Department of Health and Social Services**, Bureau of **Vital** Records.

II

MARINE TRANSPORTATION

This chapter presents the individual factors needed to define the marine transportation portion of the Base and OCS Cases, which were described generally in Chapter **I**, and illustrated earlier by curves "B" and "**C**" in **Figure 1**. **With** respect to the Base Case, marine transportation demands include those of the present economy, as extended into the future, plus **those** generated by OCS development in the Norton, **Navarin**, and St. George lease sales areas. OCS Case transportation demands add those generated by OCS development in the North Aleutian sale area.

In the Bering Sea region, marine transportation currently serves as the primary distribution system for consumer goods and industrial equipment, **as** well as a market oriented transportation system **for** the fishing industry. The marine transportation system is expected to continue to serve such demands throughout the forecast period. With the advent of OCS development, marine transportation services expand adding the movement of OCS related supplies and equipment into and within the various lease areas, and, if recoverable oil and/or gas resources are found, also adding the movement of crude products to market.

Since the methodology is to be applied by persons who are without formal

training in transportation planning, the approach has been simplified. With respect to marine transportation, a basic premise of the methodology is that two factors can be used to measure impacts at a particular port: 1) the ratio between local tonnage demand and port tonnage handling capacity; and 2) local vessel activity. The changes in the tonnage demand/capacity ratio are used to evaluate cargo handling facilities and services, while changes in vessel activity are used to evaluate the adequacy of berthing space and port traffic problems. Together, both factors contribute to an evaluation of a port's capability to handle future marine transportation demands.


Estimates of existing handling capacity for ports in the Aleutian region have been made in prior Social and Economic Studies Program reports (see Technical Report 52 - Peat, Marwick, Mitchell & Co. and J. Lindsay & Assoc., 1980; Technical Report 58 - Peat, Marwick, Mitchell & Co. and ERE Systems, Ltd., 1981; Technical Report 66 - ERE Systems, Ltd., 1982; and Technical Report 84 - Louis Berger and Assoc., 1983) and other documents (see Alaska Consultants, Inc. and PRC-Harris, Inc., 1981). Consequently, the focus of this discussion is on calculating the numerator portion of the demand/capacity ratio and determining the number of vessel trips with and without the proposed North Aleutian lease offering. In the discussion that follows, the determination of tonnage demands and vessel trips are presented in separate sections and each port is treated individually. Since OCS activities can be expected

to be focused at one or several ports, the methodology addresses the key ports of **Unalaska/Dutch** Harbor, Cold Bay, **St.** George Island, and St. Matthew **Island**. This information is organized so that the Base Case and OCS Case formulas are separately developed.

Marine Tonnage Demands

Marine tonnage demand is typically measured as "Throughput Tonnage", which is defined as the sum of all cargo movements into and out of a port. A representation of this definition of throughput tonnage is illustrated in version [A] of the general formula in Figure 3. For accounting purposes, inbound and outbound tonnage demands can be divided into any number of categories, the number depending on the functions of the port or the kinds of cargo moved through the port. For example, **Unalaska/Dutch** Harbor is a major transshipment port for petroleum products, producing high **liquid** bulk volumes both inbound and outbound; while Cold Bay, which receives large quantities of various aviation fuels due to the community's aviation function, produces only high inbound liquid bulk volumes. The ability to represent various categories in the formulas, however, is more **likely to** be based on the ability to identify relevant data for each type cargo movement. **It** is assumed, for the categories discussed in this analysis that detailed data about historic tonnage movements can be obtained from the publication, "Waterborne Commerce of the United States" (see U.S. Army,

FIGURE 3
GENERAL ORMU FOR THROUGHPUT MARINE TONNAGE



SOURCE: ERE SYSTEMS, LTD.

Corps of Engineers, annual).

In communities such as **Unalaska/Dutch** Harbor or Nome, significant volume of cargo **to** surrounding **regional** villages, version **[A]** of the general formula in Figure 3 must be modified. In a transshipment port, inbound tonnage must be calculated from separate estimates of outbound transshipped tonnage and inbound tonnage destined **only** for the port itself but not transshipped (referred to as "locally consumed"). This allows separate assessments of the economic factors that influence the transshipment service area and those that influence the port community itself. Substituting this relationship for inbound tonnage in version **[A]** of the formula in Figure 3, produces version **[B]**, and after transposing terms gives the relationship in **version [C]**.

BASE CASE

The Base Case tonnage forecast provides the basis for subsequent comparative analysis. A Base Case forecast must be prepared for each of the principal ports **likely** to be affected by **an** increase in OCS development activities. In the Aleutian region, the ports that must be included are: **Unalaska/Dutch** Harbor, **Cold** Bay, St. George Island, and St. Matthew Island. The circumstances at each port and the appropriate formula for determining tonnage demands are discussed in the following subsections.

Unalaska/Dutch Harbor

Generally, **Unalaska/Dutch Harbor** is expected to continue its principal transshipment function. Thus the port is expected to continue to handle all petroleum products redistributed to western and northwestern Alaska, as well as southwest Alaska, whether for OCS or non-OCS development purposes. The port is also expected to be the major collection point in southwest Alaska for the shipment of fish products to foreign and Lower 48 ports.

The general formula for throughput tonnage at Unalaska/Dutch Harbor is given in Figure 3, formula version [C], presented earlier. Due to the complexity of functions and activities at Unalaska/Dutch Harbor, those portions of the formula pertaining to outbound and inbound tonnage demands must be greatly expanded and, in this analysis, separate formulas are used to represent each. These separate formulas are simply expanded subsets of the general formula in Figure 3 and may be substituted in that formula.

Outbound Tonnage. Several versions of the formula for Base Case outbound marine tonnage at Unalaska/Dutch Harbor are given in Figure 4. Version [A] shows in a simple fashion the three principal components: outbound tonnage attributable to demands made by villages in the transshipment service area; outbound tonnage generated locally (primarily fish products); and outbound tonnage generated by offshore

FIGURE 4

FORMULA FOR BASE CASE OUTBOUND MARINE TONNAGE
AT UNALASKA/DUTCH HARBOR





FIGURE 4 (Continued)


FORMULA FOR BASE CASE OUTBOUND MARINE TONNAGE AT UNALASKA/DUTCH HARBOR



SOURCE: ERE SYSTEMS, LTD.

FIGURE 4 (Continued)

FORMULA FOR BASE CASE OUTBOUND MARINE TONNAGE AT UNALASKA/DUTCH HARBOR



VERSION "D"

FIGURE 4 (Continued)

FORMULA FOR BASE CASE OUTBOUND MARINE TONNAGE
AT UNALASKA/DUTCH HARBOR





FIGURE 4 (Continued)

FORMULA FOR BASE CASE OUTBOUND MARINE TONNAGE
AT UNALASKA/DUTCH HARBOR






FIGURE 4 (Continued)

FORMULA FOR BASE CASE OUTBOUND MARINE TONNAGE
AT UNALASKA/DUTCH HARBOR



oil and gas development activities in the Norton, Navarin, and St. George Basin lease areas. Version [B], Figure 4, redefines [A] in terms of cargo categories and version [C] expands [B] to reflect geographical considerations. In version [B], the cargo categories reflect the major cargo handling categories at **Unalaska/Dutch Harbor**.

The principal non-OCS related outbound products are petroleum and **fish**. Petroleum products are distributed **to** other transshipment ports throughout western and northwestern Alaska **or to** smaller **villages** in the **Aleutians**, as shown in the first component of version [C], **Figure 4**. Fish products are distributed to Lower 48 and Far Eastern foreign ports with no geographical differentiation in the formula. The remaining elements in **the** first component of **version [B]** collects non-OCS related dry **cargo** and any other non-OCS related bulk products into a **single** category.

With respect to OCS related outbound tonnage, differentiation is made with respect to petroleum or non-petroleum products in formula version [B], and these are expanded further by **lease offering area in version [C]**.

The final transformation of this outbound tonnage formula **is given in version [D], Figure 4**. The individual components are more fully explained in the following paragraphs. For reference purposes, each

component in Figure 4 is identified by a corresponding number in the following text.

Local Economy. Outbound tonnage from the local economy is represented in Figure 4 by components beginning with the number "1". The factors in Group 1 represent outbound tonnage demands generated in the various regional areas served through Unalaska/Dutch Harbor. Group 1 also includes factors that reflect regional export of commercial fishing products. Group 2, represented in Figure 4 by components beginning with the number "2", deals with the demands of the petroleum industry in the Norton, Navarin, and St. George lease areas. The characteristics of Group 2 are discussed later.

1.A.1.a. Base year outbound tonnage demand for western and northwestern Alaska areas serviced through Unalaska/Dutch Harbor is determined from an analysis of historic tonnage demand data. Historic outbound tonnage data for Unalaska/Dutch Harbor must be collected in a way that allows the researcher to separate outbound tonnage delivered to western and northwestern ports and to all other ports. From a time series of such data it is possible to determine the current trends in tonnage growth using regression analysis. If sufficient historic data is available to give acceptable statistical tests, and the forecast economics do not

indicate rapid or widely fluctuating growth, the resulting regression equation **could** be used to generate the factor **1.A.1** without separately developing the "a" and "b" **subfactors**.

In the absence of acceptable statistical results, the regression equation could be used **to bring the** historic data forward to the base year selected for starting the analysis. This **is** necessary because **Corps of Engineer data (see U.S. Army Corps of Engineers, annual) typically lags** the current date by **two** to three years. Then, the growth factor technique (see **below**) or some other approach **could** be **used** to generate the **forecast**.

1.A.1.b. The population in western and northwestern Alaskan areas served through Unalaska/Dutch Harbor is some fraction of the cumulative populations of the North Slope Borough, Nome, Wade Hampton, and Bethel census areas. In Technical Report 58 (Peat, Marwick, Mitchell & Co. and ERE Systems, Ltd., 1981), it was assumed that 80 percent of the cumulative population of these census areas was served through Unalaska/Dutch Harbor. **These population data are presumed to be determined as part of the MAP Model output.** Growth factors for this composite population are developed by dividing a given horizon year population by the base year population. The base year tonnage demand is multiplied by the growth factor **for each year to estimate tonnage demand for that**

year.

The inherent assumption in this approach is that increases in transportation demand are proportional to population. However, the researcher may want to consider an additional factor which reflects that rising income levels (if applicable) are likely to produce slight increases in per capita tonnage demand. This entails adding a multiplier reflecting the expected average annual increase due to income or some other related characteristic. This element would be referenced as 1.A.1.c., but is not illustrated in Figure 4.

1.A.2.a. This factor is similar to that developed for 1.A.1.a. except this reflects trends in the southwest regional area serviced through Unalaska/Dutch Harbor. Historic outbound tonnage to this southwest region is evaluated using regression analysis and a base year tonnage estimate can be established as described in 1.A.1.a. above.

1.A.2.b. The population in the southwest service area is presumed to be determined separately from this analysis. The southwest service area encompasses the Bristol Bay Borough, Dillingham, and Aleutian census areas. Growth factors are developed as described above in 1.A.1.b.. As mentioned above, a

third factor reflecting income or other related characteristic could be included.

1.B.1. Fishing products are a major outbound commodity at Unalaska/Dutch Harbor. Although tonnage estimates could presumably be developed for each fish species, in this analysis fish products tonnage is consolidated into traditional and underutilized species (groundfish). Component 1.B.1. treat% the traditional fish products. Since the State of Alaska and several federal agencies have an interest in fish economics, it is assumed that estimates of future fish volumes will be generated outside the framework of this analysis. Depending on the source, these future estimates may have to be converted from round weight to processed weight.

1.B.2. This category treats the underutilized fish species, exclusively. The groundfish segment is currently considered the fastest growing sector of the commercial fishing industry in this region of Alaska. Various fishing activity forecasts prepared by others have demonstrated a broad diversity of opinion regarding future growth potential for this segment of the industry. For this analysis, it is assumed one of the analyses done by others will be selected and used to derive **annual levels** of processed groundfish products (see Earl R. Combs, Inc., 1981) .

the fuel requirement for a 15,000 foot exploration well. For this analysis, a 3050 meter (10,000 foot) well depth is assumed for each of the three prior lease sales (Dames & Moore and Harrison, G.S., 1982). The figures in Table 1 must be proportionally adjusted to reflect the lessor depth. The resultant fuel requirement per well is multiplied by the total number of exploration wells operating in the three lease offering areas each year.

2.A.2.a., b., and c. The annual number of exploration wells in the Norton, Navarin, and St. George Basins are determined by MMS independent of this effort. It should be noted that the formula in Figure 4 assumes all of the well supplies move through Unalaska/Dutch Harbor. If this is contrary to the final set of assumptions for the combined lease offerings, appropriate adjustments must be made.

2.B.1. The fuel requirement for production wells is also shown in Table 1. This figure must be proportionally adjusted to correspond to the assumed 10,000 foot well depth.

2.B.2.a., b., and c. The annual number of production wells in the Norton, Navarin, and St. George Basins is determined by MMS independent of this effort.

2.C.1. The fuel requirement for workover wells is given in Table 1. This figure must be proportionally adjusted to correspond to the assumed 10,000 foot well depth.

2.C.2.a., b., and c. The number of workover wells in the Norton, Navarin, and St. George Basins is determined by MMS independent of this effort.

2.D.1.a. Dry cargo requirements for an exploration well can also be found in Table 1. These requirements combine the tubular goods, drilling mud, cement, and miscellaneous consumables. Component 2.D.1.a. is for tubular goods. The figures in the table must be proportionally adjusted to the assumed well depth.

2.D.1.b. Drilling mud can be reused from well to well. The figures in Table 1 are based on an assumption that the mud is used in up to four wells. After the depth adjustment has been applied, the resultant figure must be divided by four to obtain the per-well data.

2.D.1.c. Cement tonnage for an exploration well comes from Table 1 and must be adjusted for the assumed well depth.

2.D.1.d. Miscellaneous consumables tonnage for an

exploration well comes from Table 1 and must be adjusted for the assumed well depth.

2.D.2.a. through 2.D.2.c. These factors are the same as 2.A.2.a. through 2.A.2.c.

2.E.1.a. through 2.E.1.c. These factors are the same as 2.D.1.a. through 2.D.1.c., except the figures come from the column labeled "production well" in Table 1. As with other figures from this table, an adjustment must be made for the assumed well depth.

2.E.2.a. through 2.E.2.c. These factors are the same as 2.B.2.a. through 2.B.2.c.

2.F.1.a. through 2.F.1.d. These factors are the same as 2.D.1.a. through 2.D.1.c., except the figures come from the column labeled "workover well" in Table 1. As with other figures from this table, an adjustment must be made for the assumed well depth.

2.F.2.a. through 2.F.2.c. These factors are the same as 2.A.2.a. through 2.A.2.c.

2.G. Fuel and other petroleum products are needed for the work boats. As a rule of thumb, such fuel requirements are



estimated as being equal **to** the total **fuel demand for drilling the various wells**. However, if the **fuel** requirements of each work boat **can be** estimated from boat operating characteristics, then a more informed estimate **might be** derived by multiplying that estimate by the number of work boats. Greater refinements of **this approach could be achieved if the fuel demands were linked to boat trips**. In which **case**, estimates of the number and **length** of boat trips **would have to be made**.

Inbound Tonnage. Inbound marine tonnage at **Unalaska/Dutch Harbor** for the Base Case is given **by** the formula in **Figure 5**. Generally, inbound tonnage includes tonnage **ultimately** shipped outbound plus tonnage that comes in and is **consumed** locally. **Version [A] of the formula illustrates these two principal components**. The outbound tonnage component was discussed in the preceding section. The focus of this discussion is on tonnage consumed locally (**i.e. in Unalaska/Dutch Harbor**). In version [B] of the formula in **Figure 5**, this second factor is expanded to reflect two basic elements of marine tonnage: bulk petroleum and dry cargo products. These elements are further explained in the following text.

Bulk Petroleum. Bulk petroleum products consist mostly of refined fuels and **oils** including automotive and aviation gasolines, heating **fuels**, lubricating **oils**, and other such products moved and

FIGURE 5

FORM A FOR BASE CASE INBOUND MARINE TONNAGE
A. UNALASKA/DUTCH HARBOR



stored in bulk. Large quantities of fuel in **55 gallon drums also constitutes** a bulk product.

2.A.1. From a historical perspective, the difference between inbound petroleum product tonnage and petroleum product tonnage transshipped provides a measure of the petroleum tonnage consumed locally. This relationship can be seen by taking factor 1 in version [A], Figure 5, and transposing it to the other side of the equal sign. Since this component can be derived from historic data, regression analysis or the growth factor technique can be employed to develop a forecast. Relevant historic information is found in waterborne commerce data published by the Corps of Engineers (see U.S. Army Corps of Engineers, Annual).

2.A.2. The population referred to here is the population of **Unalaska/Dutch Harbor and adjacent road connected areas.** A population forecast for **Unalaska/Dutch Harbor** could be available from MMS or other Social and Economic Studies Program contractor. Growth factors are developed as described earlier for element **1.A.1.b.**, Figure 4, outbound tonnage. The use of the growth factor technique may be inappropriate if industry is the principal user of petroleum products in place of the local population. When industry is the principal user, it may be more appropriate to develop growth factors for the specific industry and

use those in place of population growth factors. If both industry and population are relatively significant, a weighted average of the two set of growth factors should be used.

Dry Cargo. The term "dry cargo" products as used in this analysis consists of any product not falling into the bulk petroleum category.

2.B.1. Base year dry cargo tonnage consumed locally is derived from historic dry cargo tonnage data in the same manner described above for petroleum tonnage (reference 2.A.1., Figure 5).

2.B.2. Dry cargo tonnage has a high correlation with population level. Since the focus is on locally consumed goods, population estimates should include both permanent and on-site transient people. In Unalaska/Dutch Harbor, the transient segment should include all on-site fishing employment. Growth factors are developed as described in reference 1.A.1.b., Figure 4.

Cold Bay

The primary economic function of Cold Bay in the southwest region is as an aviation hub for Aleutian Island communities. The port at Cold Bay serves no transshipment function and, thus, has little or no outbound tonnage. This simplifies calculations, since the outbound tonnage

factor in the formula in version [A], Figure 3, becomes zero and throughput tonnage then **equals** inbound tonnage. Similarly, in calculating inbound tonnage, version [A], Figure 5, outbound tonnage becomes zero and inbound tonnage (and, therefore, throughput tonnage) **equals** tonnage consumed **locally**. **In** this framework, the discussion above pertaining to locally consumed tonnage, formula version [B], Figure 5, applies to the Cold Bay analysis. The **major** difference is in developing the growth factors for elements **2.A.2.** and **2.B.2.** **In element 2.A.2.**, the expansion of petroleum product tonnage **in** Cold Bay is **linked** principally to growth in aircraft operations and **only** secondarily to population. Aircraft operations data for this analysis **should** come from the aviation analysis presented **later** in this report. **In element 2.B.2.**, transient aviation or OCS personnel rather than transient fishermen are the relevant population issue.

St. George Island

Based on the scenario of events for the Norton, **Navarin**, and St. George Lease Sale areas, as described in Chapter 1, **St. George Island** is expected to function **as** the jumping off point for the offshore work force employed in the **St. George Basin**. This **implies** the stationing of two or more helicopters at St. *George* Island and requires start-up operations of a shuttle aircraft from Cold **Bay**. These aviation activities increase fuel utilization at St. George Island. **Dry** goods tonnage and heating fuel demands should also increase due to the

stationing of aircraft crews and **related** support personnel. **As long as St. George** Island supports no fishing operations, **it** has **no** outbound tonnage demands, **so** the determination **of** throughput tonnage is reduced to determining the **volume of locally** consumed tonnage, **as was done for Cold Bay**. The required calculations **are** represented **by locally** consumed petroleum and dry goods components (2A and 2B, respectively) **in** formula version [B], Figure 5. The assessment **of** aircraft operations **at St. George** Island, performed **later** in **this** methodology, **should** provide a **clue as** to whether population or aviation **growth** factors, or some weighted average, **should be utilized in** determining petroleum tonnage. The potential addition **of groundfishing** activities **at St. George Island** will also have to **be** considered **in** determining affects **on** population and, subsequently, **on** petroleum **product usage**. The factors influencing **dry cargo** tonnage **are similar to those** described **earlier** for **Unalaska/Dutch Harbor**.

St. Matthew Island

During the exploration, development, and production phases of activities in the Navarin Basin, St. Matthew island is assumed to be used as a forward marine support base. **In addition to storing the various drilling materials (mud, cement, etc.), it is expected that fuel for the** work boats, platforms, and generators **will be maintained at the base**. The inbound **fuel** requirements **for the** platforms, work **boats**, and helicopters can be calculated from parts **of formula** version [D], Figure

- 4. Exploration, production and workover wells are serviced, so only components **2.A., 2.B., 2.C., and 2.G.** are applicable to the fuel calculations. Within these components, the number of wells serviced in the Norton and St. George lease areas goes to zero and elements **2.A.2.a., 2.a.2.b., 2.B.2.a., 2.B.2.b.,** as well as **2.C.2.a.** and **2.C.2.b.,** dropout. Only elements **2.A.1., 2.A.2.c., 2.B.1., 2.B.2.c.,** together with **2.C.1. and 2.C.2.c.,** need be calculated, then repeated to get **2.G..**
- Dry cargo tonnage at the **St. Matthew** base can be calculated from components **2.E.** and **2.F.** in formula version [D], **Figure 4. Elements 2.E.1.a.** through **2.E.1.d. and 2.E.2.c.** provide data for production wells; elements **2.F.1.a.** through **2.F.1.d. and 2.F.2.c.** provide data for workover wells. Additional dry cargo tonnage will be generated during construction of the service base. However, insufficient information about the character of the base prevents calculating the related tonnage at this time.
- If the petroleum products and dry cargo products for the **Navarin** Basin are shipped directly to the marine service base instead of through **Unalaska/Dutch Harbor,** the tonnage figures previously developed for **Unalaska/Dutch Harbor** must be reduced. This is accomplished by dropping elements pertaining to the number of **Navarin** Basin production and workover wells.
-
-

Aleutian Transshipment Terminal

Based on assumptions presented earlier in this report, an Aleutian Transshipment Terminal would be established to handle crude oil from the St. George and Norton Basins. Resources from the St. George Basin would be piped to the terminal; resources from the Norton Basin are transported from the lease area to the terminal in ice strengthened shuttle tankers. The crude oil would be stored and subsequently shipped to Lower 48 markets in VLCC tankers. Based on these expected resource movements, inbound marine tonnage to the terminal equals the annual output of recoverable resources for the Norton lease area, while outbound marine tonnage equals the combined annual output of recoverable resources from the Norton and St. George lease areas,

Resources recovered from the Navarin Basin are assumed to be shipped directly to Lower 48 refineries by ships loading at an offshore terminal located in that lease offering area. The quantity of resources shipped is assumed to equal the annual production from this basin. Information pertaining to the quantity of resources recovered is developed by MMS as part of the scenario prepared for the prior lease sales. If Navarin Basin resources are shipped by marine carriers through the Aleutian Transshipment Terminal, the annual production of the basin must be added to the inbound and outbound tonnage calculations for the terminal,

OCS CASE

The OCS Case assumes the **addition of** North Aleutian Basin economic activities **to** those of **the Base Case**. **In this** situation, certain development changes are assumed to take place. The principal change is that after exploration is complete in the North Aleutian Basin and a decision is made to proceed with development, a supplemental marine base is constructed to support the North Aleutian activities. Primary staging of marine support **to** the North **Aleutian area will** continue to **occur** at **Unalaska/Dutch** Harbor.

However, because the location of this new base is **closer** to Lower **48** ports than **Unalaska/Dutch** Harbor, and because direct shipments reduce handling at **Unalaska/Dutch** Harbor, it may be more efficient to ship some products directly to the base instead of through **Unalaska/Dutch Harbor**. **To** the extent these products can be identified and measured, in terms of product tonnage, inbound and outbound tonnages **at Unalaska/Dutch** Harbor **can** be adjusted. On the other hand, the advantages of shorter distance and reduced handling could be offset by physical limitations of the harbor and/or dock facilities at the new base. Both circumstances must **be** evaluated when greater details about the North Aleutian scenario are available.

Unalaska/Dutch Harbor

During the exploration period in the North Aleutian Basin, outbound tonnage demands at Unalaska/Dutch Harbor should increase over Base Case levels because an additional volume of petroleum products and dry cargo will be moved. To reflect this added volume, several elements need to be added to formula [D], Figure 4. Specifically, the number of exploration wells in the North Aleutian Basin should become element 2.A.2.d. and element 2.D.2.d.. If petroleum products are transshipped through Unalaska/Dutch Harbor during the development and production phases of the North Aleutian Basin, the number of development wells should become element 2.B.2.d. and the number of production wells should become element 2.C.2.d.. If petroleum products for the North Aleutian Basin are shipped directly to the new marine support base, along with dry cargo products, outbound tonnage at Unalaska/Dutch Harbor will be reduced or will grow more slowly. Other changes in formula [D], Figure 4, relate to the use of population or industrial growth factors. Due to the additional economic activities, the annual growth factors are expected to increase slightly and these revised factors should be substituted for the Base Case factors.

Inbound marine tonnage demands at Unalaska/Dutch Harbor continue to be governed by formula [B], Figure 5. The only significant change is the substitution of new growth factors for Unalaska/Dutch Harbor.

Cold Bay

Aviation activities at Cold Bay should increase with the added economic activities of the North Aleutian Basin. The **OCS** Case for Cold Bay continues to be represented by formula [B], Figure 5. Due to the importance of aviation to Cold Bay, aviation growth factors should probably be used in element **2.A.2.**, in place of population growth factors. Revised growth factors reflecting **OCS** related population changes should **also** be substituted in element **2.B.2.**.

St. George Island

Unless some change is made regarding aviation operations assumptions or assumptions pertaining to population **levels** on **St. George** Island, the **OCS** Case calculations **will** be identical to those for the Base Case. **In** short, no changes are expected at **St. George Island** as a **result of the** North Aleutian **lease** offering.

St. Matthew Island

No changes are expected **at St. Matthew Island** as a **result** of the North Aleutian Lease offering.

Aleutian Transshipment Terminal

Resource production from the North Aleutian Basin is expected to be piped to the Aleutian Transshipment Terminal. Thus no increase is expected in inbound marine tonnage. Outbound marine tonnage will, however, reflect the added volume each year of expected North Aleutian lease area field production, as determined by MMS in the North Aleutian petroleum development scenarios,

Marine Vessel Requirements

Marine vessel requirements are measured as the number of vessel round trips required to serve expected tonnage demands. The general formula for vessel round trips is given in Figure 6, version [A]. Because there are several different combinations of vessel capacity and tonnage demand categories, the formula in version [A] transposes in version [B] to a summation of the different combinations. In this latter version, the term "xy" is used to identify the different combinations of vessel capacity and tonnage demand categories. The variable "x" denotes the range of tonnage demand categories; the variable "y" denotes the range of vessel capacities. Some of the more common combinations used in prior SESP studies are illustrated in Table 2.

Additional vessel trips are related to the movement of rigs, platforms, construction equipment and accommodation barges, pipeline laying and

FIGURE 6

GENERAL FORMULA FOR DETERMINING VESSEL ROUND TRIPS

Diagram (A) illustrates the general formula for determining vessel round trips. It consists of three rounded rectangular boxes arranged horizontally. The first box on the left contains the text "VESSEL TRIPS". To its right is an equals sign (=). The second box contains the text "TONNAGE DEMANDS". To its right is a division symbol (÷). The third box contains the text "VESSEL CAPACITY". To the right of the entire expression is the label "(A)".

Diagram (B) illustrates a detailed formula for determining vessel round trips. It consists of three main components arranged horizontally. The first component is a rounded rectangular box containing the text "VESSEL TRIPS". To its right is an equals sign (=). The second component consists of two summation symbols (Σ) placed side-by-side. Below the first summation symbol is the text "X → m", and below the second is "Y → n". To the right of these summation symbols is a large rounded rectangular box containing a division symbol (÷) between two smaller rounded rectangular boxes. The left smaller box contains the text "TONNAGE DEMANDS FOR CATEGORY XY", and the right smaller box contains "VESSEL CAPACITY FOR CATEGORY XY". To the right of the entire expression is the label "(B)".

SOURCE: ERE SYSTEMS, LTD.

TABLE 2

EXAMPLES OF THE RANGE OF VESSEL CAPACITIES (1)

<u>VESSEL TYPE</u>	<u>AVERAGE CAPACITY</u>
<u>Fishing Boats</u>	28 short tons
<u>Barges</u>	
Dry Cargo Barge	6,000 short tons
Tanker Barge	7,000 short tons
<u>Lighters</u>	
Dry Cargo	24 short tons
Tankers	38 short tons
<u>OCS Work Boats</u>	
Dry Cargo Exclusively	400 short tons
Bulk Fuel and Water	780 short tons
<u>Tankers</u>	
Intra Coastal	35,000 short tons
Shuttle Tankers.	75,000 short tons
VLCC Tankers	250,000 short tons

 NOTE : (1) The "average tonnage delivered" or
 "average tonnage loaded" by
 tankers and general cargo ships
 should be used in place of vessel
 capacity to calculate number of
 vessel trips.

SOURCE: ERE Systems, Ltd.

related supply and hopper barges, as well as the movement of OCS facility modules such as gas separation units. The number of vessels assumed to be involved in these various OCS activities is illustrated in **Table 3.**

BASE CASE

Marine vessel movements are calculated for **bulk fuel** and dry cargo tonnage categories. Since the type of **vessel** is **likely** to be different **inbound and outbound, separate calculations are performed for each direction.**

Unalaska/Dutch Harbor

This community has a single **bulk fuel** facility that receives **fuel** shipments delivered by commercial tankers of 35,000 dwt average size. Regardless of the ultimate use of the **fuel**, it **is assumed** **bulk fuel** deliveries **will** be made in the same fashion throughout the forecast period. To determine the number of vessel round trips, inbound fuel demands calculated **earlier** for the Base Case must be **summed** and divided by the 35,000 dwt tanker capacity. More specifically, the researcher should add elements **1.A.1., 1.A.2., 2.A., 2.B., 2.C., and 2.G.** presented in the outbound tonnage formula, version [D], Figure 4, and element **2.A.** presented in the inbound tonnage formula, version [B], Figure 5. For each year of the forecast, the populations in the various areas serviced

TABLE 3

ASSUMED NUMBER OF MARINE VESSELS FOR SPECIFIC OCS ACTIVITIES

<u>CATEGORY</u>	<u>NUMBER AND TYPE VESSEL</u>
Rig or Platform	1 Rig/Platform 8 Supply/Anchor/Tug Boats
Construction Camp	3 Accomodation Barges 3 Construction Equipment Barges 3 Tug Boats
Pipelaying Construction Spread	2 Dredges 4 Hopper Barges 1 Accomodation Barge 3 Tug Boats
Modular Equipment	15 Barges assigned per year.

SOURCE : ERE Systems, Ltd.

- and the number of wells serviced in each lease area should reflect the role of Unalaska/Dutch Harbor as assumed by the researcher.

Outbound fuel shipments must be **calculated separately for each outbound fuel** category because different **kinds of vessels provide the** transportation. **Fuel shipments to villages in western and northwestern Alaska** and in the Aleutian region are assumed to be made in 7,000 ton capacity tanker barges. Elements **1.A.1.** and **I.A.Z.**, as presented in the outbound tonnage formula, **version [D]**, Figure **4**, are summed and divided **by the 7,000 ton capacity of** these barges.

Fuel used on the rigs and platforms in the Norton, St. George, and **Navarin** lease **areas** is assumed to be delivered **to the respective support** base in 7,000 ton tanker barges and from there **to the rigs/platforms in** OCS work boats. The calculation of the number **of barge trips is based** on dividing total fuel requirements, including work boat fuel demands, by the 7,000 ton capacity of the barges. Assuming **all fuel** for OCS needs is distributed from **Unalaska/Dutch** Harbor, the researcher needs to sum elements **2.A., 2.B., 2.C., and 2.G.**, as presented **in** the outbound tonnage formula, **version [D]**, Figure **4**. With respect to OCS work boat trips, only the fuel requirements of the rigs/platforms is considered, elements **2.A., 2.B., and 2.C.**. The fuel cargo capacity of these work boats is assumed to be about **718** tons. Dividing total rig/platform **fuel** demands by the work boat fuel capacity gives work boat round trips.

During the later stages of the development phase and during the production phase, rig/platform fuel demands might be reduced or eliminated by burning the free gas typically found with crude petroleum products (New England River Basins Commission, 1976). Such demands might also be reduced by treating the crude petroleum sufficiently to use in specially designed equipment. Employment of either technique requires the researcher to adjust the annual rig/platform fuel demands by some percentage of offset.

The maximum number of work boat trips may be governed by OCS needs other than fuel, such as drill water. Drill water requirements for a 15,000 foot well are stated in Table 1. These water requirements are considerably greater than those for fuel, yet the drill water capacity of the work boats is less. The implication is that drill water related tripmaking could be almost 13 times greater than the trip requirements for fuel. However, some of these tripmaking requirements for drill water are offset by the fact that most rigs or platforms have the capacity to produce drill water from the ocean (Kramer, L.S., Clark, Vet., and Canelos, G.J., 1978). The particular characteristics of the rigs/platforms for each lease area need to be examined in order to determine the appropriate number of drill water trips and whether or not these should be used in place of expected fuel trips to capture the upper limit of trip requirements.

With respect to dry **cargo vessel** movements at **Unalaska/Dutch Harbor** several categories must be considered. Foremost is the catching and regional exporting of fish products. Also included are dry cargo shipments supporting local population demands at **Unalaska/Dutch Harbor** and those shipments supporting OCS needs in the Norton, St. George, and **Navarin lease** sale areas.

Fishing activities at **Unalaska/Dutch Harbor** are responsible for only some defined percentage of total fish caught and processed in the Aleutian - Bristol Bay region. An estimate of fishing boat activity at **Unalaska/Dutch Harbor** can be developed either from a forecast of round weight of fish by species or from a forecast of catch by vessel type. Dividing the catch size (in terms of weight) by an average vessel catch size per trip or vessel capacity produces an estimate of the number of round trips by fishing vessels.

The export of processed fish to foreign and Lower 48 ports will also generate vessel trips. The number of trips can be estimated from forecasts of processed fish tonnage, which are identified as elements **1.B.1.** and **1.B.2.** in the **outbound marine tonnage formula, version [D]**, Figure 4. In Technical Report 58 (Peat, **Marwick**, Mitchell & Co. and ERE Systems, Ltd., 1981), it was assumed each outbound cargo vessel carried an average of 150 short tons of dry cargo. To determine the number of

vessel trips, elements 1.B.1. and 1.B.2. are summed and divided by the 150 ton average cargo per trip.

It should be noted that a distinction is made here between vessel capacity and the average size of cargo loaded or unloaded. Commercial cargo ships and tankers travel from port to port picking up and delivering products. When arriving at a particular port the ship may be empty, loaded to capacity, or any point in between. A particular ship is unlikely to either empty all its cargo or to fill available capacity at any one port. In order to model this characteristic, this methodology employs the terms "average tonnage delivered" and "average tonnage loaded". An estimate of the values of these terms for a given port can be derived by dividing total product tonnage inbound and outbound by the total number of vessels of a particular type calling on the port. For example, in Unalaska/Dutch Harbor dividing total dry cargo tonnage inbound and outbound by the number of dry cargo ships calling on the port gives average dry cargo tonnage delivered and loaded, respectively. The long term trend in an improving economy should be that these averages increase over time, but this must be verified through a review of historic data to determine the direction of this trend. In Unalaska/Dutch Harbor one would expect to find this trend tied to the fortunes of the fishing industry.

Inbound dry cargo tonnage demands of the local population are developed

in element **2.B. of the inbound marine tonnage formula, version [B], Figure 5.** Based on an analysis of historic data, it was assumed in Technical Report 58 (Peat, Marwick, Mitchell & Co. and ERE Systems, Ltd., 1981) that each cargo vessel visiting Unalaska/Dutch Harbor delivered an average of 65 short tons per trip. To arrive at an estimate of inbound vessel trips at Unalaska/Dutch Harbor, the annual tonnage demands given in element **2.B.** are divided by the 65 ton average cargo per trip.

The movement of OCS dry cargo supplies into and out of Unalaska/Dutch Harbor may generate significant levels of vessel activity. Inbound deliveries to the OCS service base are as likely to be made by scheduled commercial carriers as by special contract carriers. The range of inbound vessel trips can be derived by dividing bulk and dry cargo inbound tonnage, first, by the average tonnage delivered, and second, by 6,000 short tons, the assumed average maximum capacity of inbound cargo barges. It should be noted here that the average tonnage delivered per ship will rise significantly when OCS contract ships deliver their entire cargo. Outbound shipments to the smaller, sale specific, marine support bases are expected to be made by contract carriers utilizing the full capacity of the vessel. Outbound shipments to the rigs and platforms in the St. George Lease area are expected to be made by OCS work boats. The volume of tonnage to be moved is estimated in elements **2.D., 2.E, and 2.F.** of the outbound marine tonnage formula, version [D],

Figure 4. For each year of the forecast these elements should reflect the degree of support provided by the base at Unalaska/Dutch Harbor. The number of vessel trips each year can be estimated by summing these elements and dividing by the appropriate ship capacity or average cargo figure.

The range of outbound vessel trips can be estimated by dividing the outbound tonnage by either the work boat deck cargo capacity of 350 short tons, or the average tonnage loaded. With regard to work boat trips, fuel and drill water resupply requirements should be checked against the other capacities of the work boat. In particular, if drilling mud is delivered to the rig or platform in a premixed form, it would be carried in the bulk cargo hold, which has an assumed average capacity of 140 short tons based on the weight of an equivalent volume of water. To determine the number of trips, the dry drilling mud tonnage (elements 2.D.1.c., 2.E.1.c., 2.F.1.c. in Figure 4) must be converted to an assumed liquid-state tonnage. Based upon data supplied by MMS a 10,000 foot exploration well requires about 1,300 tons of mud while a 10,000 foot. production or workover well requires about 1,100 tons of mud. Multiplying these per well demands by the number of wells serviced through Unalaska/Dutch Harbor provides an estimate of total mud tonnage demand. Dividing by the work boat's assumed bulk cargo mud capacity of 260 short tons (see Table 2) provides an estimate of vessel round trips.

Cold Bay

Marine vessel trips to and from Cold Bay revolve about the movement of fuel and cargo into the community. If a groundfish processing plant is constructed in the community, some inbound tonnage will increase by the round weight of caught fish and outbound tonnage will increase by the processed weight of the fish. The number of vessel trips generated can be calculated as follows. In Technical Report 58 (Peat, Marwick, Mitchell & Co. & ERE Systems, Ltd., 1981), the average inbound tanker was assumed to carry 3,000 short tons of fuel each trip and dry cargo ships were assumed to carry 400 short tons per trip. If a fish processing plant is located in the community, outbound cargo ships were assumed to carry 100 short tons each trip. Fishing boat vessel activities would be governed by the assumed capacities cited in Table 2. To determine vessel trips, the respective inbound and outbound tonnage demands developed earlier are divided by the appropriate ship capacities per trip.

St. George Island

The general tonnage demands and vessel movements at St. George Island are similar in type and kind to those at Cold Bay. However, assumed vessel capacities per trip are smaller: 800 short tons per trip for inbound fuel; 450 short tons per trip for inbound dry cargo. These

values are for commercial vessels. Since the island must be served by lighters, it was assumed each lighter has a capacity of about 38 short tons with the ability to handle both bulk liquids and dry cargo. Dividing fuel and dry cargo tonnage demand respectively by the commercial vessel inbound fuel and dry cargo capacities provides an estimate of line haul traffic between Unalaska/Dutch Harbor and an offloading point located offshore the island. Dividing total tonnage demand by the lighter capacity provides an estimate of vessel trips between the offshore loading point and the island.

St. Matthew Island

The operational characteristics at St. Matthew Island revolve about its use as an OCS service base for the Navarin Basin. The base is likely to be the main service point for all offshore activities and the only port for inbound aviation fuel supplies. Navigational constraints at and near St. Matthew Island are unknown, but this analysis assumes barges and work boats could be unloaded from a dock at the service base, thereby eliminating the need for lighters. From the tonnage demands developed earlier, the number of vessel trips can be determined by dividing bulk petroleum and dry cargo tonnage by the respective vessel capacities shown in Table 2: 7,000 short tons for an inbound tanker barge; 6,000 short tons for an inbound dry cargo barge. To determine the round trip movements of OCS work boats, tonnage bound for the rigs/platforms is divided by the various work boat capacity values shown

in Table 2.

Aleutian Transshipment Terminal

Oil resources inbound to the terminal via marine transportation originate in the Norton Basin. The number of such shuttle tanker trips is determined by dividing the annual production of the Norton field (expressed in tons) by the assumed tanker capacity of 75,000 dwt. Outbound resources combine the annual production of the Norton and St. George Basins. The much larger VLCC tankers are used to move these resources to Lower 48 markets. The combined production of the two lease areas is divided by the 350,000 dwt capacity of these tankers. In addition to the movement of these tankers, at least two accompanying tugs would be needed to berth the ships and provide transportation for the harbor pilot. For each tanker round trip, three additional round trips are assumed to be made by local tugs.

OCS CASE - EQUIPMENT AND SUPPLIES

The movement of OCS equipment and supplies covers a broad range of activities pertaining to OCS. Of particular interest with respect to marine transportation is a determination of the traffic generated by these various activities and their location. Specific marine activities in this discussion include work boats and tug boats, as well as other supporting vessels. These are presented separately in following

sections.

Work Boat and Tug Boat Trip Making

Work boats and tug boats support the installation of platforms, resupply of offshore facilities, offshore pipeline construction, and the docking and undocking of the shuttle and VLCC tankers. A typical work boat supporting a drilling rig or production platform in other areas of the State is characterized in Table 2. Tug boats are expected to be about half the size of a work boat, with an average crew size of 5 and no cargo capacity. Throughout the exploration, development, and production phases workboats operating in the St. George Basin will be based at Unalaska/Dutch Harbor. The number of trips made by these boats were calculated in the Base Case. Similar boats will also operate from Unalaska/Dutch Harbor during the exploration and early development phases of the North Aleutian Basin. After development of the secondary support base near the Aleutian Transshipment Terminal, these boats will primarily operate from the new support base. Total trip making for these boats is the sum of trip making for each of several different components. Each of these components are discussed in the following paragraphs.

Rig and Platform Support. Semisubmersible rigs are expected to be used for drilling during the exploration phase, while steel jacketed, ice reinforced, platforms are expected to be used during the development

and production **phases** (Dames & Moore and Harrison, **G.S.**, 1982). Both **the rigs** and platforms require **tug** and work boat support while being **towed** and positioned offshore. In addition, platforms carry a substantial **load of** deck equipment, which must be transported **to the** site and installed on deck **by** a barge mounted derrick. **Tug boats are** needed for movement of the equipment and derrick barges, while work boats are needed to maintain a supply line. Based on the development schedule suggested in **Table 2-1**, Technical Report 80 (Dames & Moore and Harrison, **G.S.**, 1982) most such **tripmaking would take place** at **Unalaska/Dutch** Harbor. **The** number of monthly work and tug boat trips in support **of** these activities is summarized in **Table 4**.

Once the **rigs** and platforms are in place and operating, work boats are used to resupply these facilities. Much of this activity is expected **to be** centered at the Transshipment Terminal support base. The factors needed **to** determine the number **of** trips generated were identified earlier in Figures **4** and **6**. However, the empirical data in Table 4 greatly reduces the calculations to determining the number of rigs or platforms being serviced monthly and the number of months of drilling activity. Seasonal drilling restrictions may be imposed, thereby limiting the actual number of months of **drilling** activity. During exploratory drilling monthly work boat trips are assumed to be 26 per rig; during developmental drilling **15** trips per platform; and during production 5 per platform.

TABLE 4
TYPICAL MONTHLY SUPPLY BOAT MOVEMENTS

<u>OPERATION</u>	<u>MONTHLY ROUND TRIPS</u>
Exploratory Drilling	26 per rig
Platform Installation	24 per platform
Developmental Drilling	15 per platform
Production Platform	5 per platform
Pipeline Lay Barge	75 per barge
Pipeline Bury Barge	25 per barge

 SOURCES: Northern Resource Management, 1980;
 Kramer, L.S., Clark, V., and
 Canelos, G.J., 1978.

Pipeline Support. Offshore marine pipelines will take several years to complete. The support requirements differ with the technique employed to lay the pipe. For this analysis, the conventional lay barge method was assumed, rather than the bottom-tow method (Dames & Moore and Harrison, G.S., 1982). These marine activities are expected to be based at the Transshipment Terminal support base. To determine the number of work and tug boat trips requires knowledge of the number of lay barge spreads, the length of the construction season, and the average number of trips per spread. Only one equipment spread is assumed. This lay barge spread is estimated to be able to lay up to 50 km (31 miles) of pipe per construction season (estimated from data in Dames & Moore and Harrison, G.S., 1982). The length of the construction season was assumed to be 180 days or 6 months. The average number of monthly round trips per lay barge spread is assumed to be between 75 and 100 depending on whether or not the bury barge is part of the spread (see Table 5).

Tanker Support. Tanker support activities, which involve the docking and undocking of the shuttle and VLCC tankers at the Aleutian Transshipment Terminal, should not affect Unalaska/Dutch Harbor, although the various tugs may put into port there from time to time. The average size of the shuttle tankers is 75,000 dwt or 0.6 MMBL (Dames & Moore and Harrison, G.S., 1982). As discussed earlier, shuttle tankers will be used between the Norton and Navarin fields and the

transshipment terminal. From the transshipment terminal, VLCC tankers, will carry the crude petroleum to Lower 48 markets. These tankers vary in size from 100,000 to 300,000 dwt (Kramer, L.S., Clark, V.C., and Cannelos, G.J., 1978). To determine the number of trips required by the tugs it is first necessary to determine the number of tanker trips per year. This latter value is arrived at by dividing the total annual field output in millions of barrels by 0.6 mmbbl, the capacity of the shuttle tanker. This result is then multiplied by an assumed number of tug boat trips per tanker visit.

When each of the individual components of work and tug boat trips are calculated and summed the result is a composite value for total trips. Depending upon how the individual components were calculated, this value may have to be adjusted. Work boats serving the offshore rigs and platforms may visit more than one facility and stop in another port before returning to its support base. If the researcher developed the work and tug boat estimate without accounting for this characteristic, an adjustment factor must also be estimated and applied to the results to reduce double counting. It was estimated the reduction could be as high as 20 percent, leaving the adjustment factor at 80 percent. However, this aspect of the estimate has already been accounted for in the empirical monthly trip observations shown in Table 4.

Other Vessel Traffic

In addition to the work and tug boats, the various barges and other ships working in the area contribute to marine traffic levels in the North Aleutian area. The major components of this additional traffic include: equipment spreads for pipelaying, support barges for additional deck equipment on the platforms, barges used to bring the construction equipment and materials for the marine terminal, and barges used to transport coated pipe for the marine feeder and trunk pipelines. An estimate of the number of these other vessels and their activities depends in part on the technology employed. Typical construction spreads can be estimated from prior Social and Economic Studies Program reports, environmental impact statements, and other special OCS related studies or reports.

OCS CASE - RESOURCE MOVEMENTS

Marine transportation is one of two alternatives considered for the movement of recovered oil and gas resources. The other alternative is a pipeline. The principal objective in evaluating the movement of these ships is to determine the additional traffic they contribute to other ship movements in the Bering Sea and in the major passes through the Aleutian Islands. The calculation of the annual number of tanker round trips was given in the previous section as part of the discussion pertaining to the use of tugs to dock and undock these ships. The

number of trips was derived by dividing the annual output of a particular field or facility, expressed in tons or millions of barrels, by the tonnage or million barrel capacity of the assumed type of ship.

III AIR TRANSPORTATION

Air transportation is the principal means for moving population in the Aleutian region. It also offers an alternative transportation mode for the movement of consumer goods, particularly perishable goods such as groceries. A similar relationship exists for OCS related activities. Air transportation is vital for moving OCS personnel between work place and residence, the latter of which is typically far from the development area. The petroleum industry also employs air transportation in the movement of important tools and equipment and supplies needed immediately.

The analysis of air transportation is conducted from both a facility and systems perspective. The facility perspective focuses on the measurement of total passenger and cargo emplacements and deplanements, as well as the measurement of total aircraft operations. At a particular facility, the emplacements/deplanements and aircraft operations can be assembled from the air transportation demands of a community's normal population and economy (hereinafter referred to as non-OCS related demands) and the air transportation demands of the petroleum industry, by lease area (hereinafter referred to as OCS related demands). When evaluating a particular facility these two sets

of demands are combined to create the Base Case and OCS Case relationship discussed in Chapter I.

The systems aspect of air travel focuses on the transshipment or through travel function. The transshipment characteristic is similar to marine travel, in that cargo or passengers may have be unloaded from one aircraft and reloaded on another to continue the journey. These same through travel cargo and passengers are also important, because they limit the space or seats available for boarding new cargo or passengers.

The material presented in this chapter discusses the methods employed to develop adequate forecasts of the Non-OCS and OCS air transportation demands and how they are combined to produce Base Case and OCS Case situations for the analysis of a particular facility.

Non-OCS Related Transportation Demands

DEFINING THE SYSTEM

At the start of this process the researcher needs to define what portion of the aviation system is to be studied. On the surface, this implies identifying the various communities to be included in the analysis. However, in identifying these communities consideration must be made for systemic relationships, the influence of potential infrastructure"

- changes, and the influence of technological changes. **To** identify included communities, these factors are initially considered **in** a synergistic manner. Subsequently, these same factors must **be** evaluated individually for **each** facility.

- **With** regard to systemic **relationships**, existing and **likely** future air transportation patterns **must** be reviewed. **Of** importance are principal origins and destinations of passengers and cargo, identification of system functions that **occur** at each airport, and the role **of** each **airport in the system**. Evolving economic patterns may also affect the **systemic relationships**, although these are often accompanied by **infrastructure changes**. For example, the growth of the **groundfishing** industry in the Aleutians may position major new processing facilities **in places** different from current major economic activities. **If** that development creates a major change in transportation demand, airlines may **alter** their schedules and/or routes to accommodate the new demand, potentially lowering the quality of service to other nearby communities.

● With regard to infrastructure changes, of particular importance are construction projects that might influence origin - destination patterns. For example, construction of a new **longer** runway or the lengthening of a runway. Such runway changes may allow landing or basing of larger aircraft, possibly changing the role of the facility in the system. Another example is construction of a new airport in support

of petroleum development or other major economic event.

With regard to technology, the changes over time tend to be more subtle. However, the Introduction of jet aircraft in place of propeller driven aircraft could be quite sudden. This substitution is a likely event in the Aleutians during the forecast period.

Sources of information about existing airport operations, numbers of flights, types of aircraft utilized, enplaned passengers, and other related data can be obtained from several sources. The Federal Aviation Administration (FAA) publishes annual summaries of aviation activity in their "Airport Activity Statistics of Certified Route Air Carriers" and long range plans for Alaska in their "Ten Year Plan - Alaska Region". The Alaska Department of Transportation and Public Facilities (ADOT/PF) sponsors aviation systems studies in major regions of the state, master planning studies of specific facilities, and studies of major problems at selected facilities. An example of the latter was a study of the runway extension at Unalaska/Dutch Harbor (see Dames & Moore, 1980b). Another source of information are the airlines serving specific communities. However, the airlines tend not to disclose information that describes their market position in a particular community.

Many of these various studies have included allowances for OCS activities in their forecasts. The researcher needs to determine, as

best possible, the nature of such activities and how they differ from the scenario **events** being used in the current evaluation. In most instances, **OCS** activities are highly generalized **in** these studies and, within the context of this analysis, **the** forecasts serve only as a standard for subsequently judging impacts.

AIR TRAVEL DEMANDS

Aviation activities fall into different categories such as scheduled commercial **services**, charter services, air freight, and general aviation, among others. To adequately assess impacts at a particular airfield, a forecast for each of **the** categories **must be** made. In the methodology that follows, this requires an understanding of the dynamics of each category relative **to** the other. **Knowing these dynamics, one can** forecast activities in one category and develop a forecast of **the** other **categories by reference to the dynamic relationship. Scheduled, commercial** services are used **as** the central tool in this methodology. This was done because commercial aviation data is most **easily** obtained and because commercial aviation is the principal category impacted by **OCS** employment. Another related reason is that the **OCS** Petroleum Employment Model (discussed later) provides a straightforward means **to** develop **OCS** employment commercial **travel** demands. The dynamic relationships of other aviation categories can be developed from historic data and from the various aviation studies and statistical

reports referenced earlier.

The principal users of the existing aviation system are assumed to be the people living or working in the region served by the system. The exception, which happens to be the rule in this analysis, is that, because of prior lease offerings, air transportation demands are likely to exceed those levels normally expected from the regional population. As discussed later, this situation is dealt with by separately evaluating OCS and non-OCS air travel demands and combining them to create the Base Case situation, which simulates conditions without the proposed North Aleutian lease sale.

It is a basic assumption of this methodology that any economic and/or population changes occurring in the region stimulate either additional or fewer demands for air transport services. Based on this approach, the researcher needs to correlate historic enplaned passenger data with regional or community population growth. This can be accomplished in a simple way by using historic data to develop a trend in per capita travel demands (trips per person per year, or per month). However, this rate must be evaluated for its applicability to future conditions, potentially resulting in some assumed annual adjustment to the ratio.

A more complex approach is to use regression or multiple regression analysis, in which case the researcher may want to introduce other

variables, such as employment or income, in addition to population.

This methodology assumes these other variables come from sources outside this analysis. In many of the smaller remote communities, data is scarce or the future situation is one of rapid change. Under these conditions, the historic data does not provide a sufficient base for regression analysis, nor do future events appear to provide a basis for saying historic patterns can be applied to future events. Consequently, a per capita trip rate is often developed as a surrogate.

Introducing the independent variable into the regression equation, or multiplying the per capita emplacement ratio by the independent variable, produces the required commercial emplacement forecast. If historic data and/or future events suggest an annual adjustment to the per capita ratio, the adjustment is applied at this time.

AIRCRAFT OPERATIONS

Emplacements are converted to aircraft operations by "loading" the emplacements onto aircraft. To accomplish this requires that several assumptions be made regarding aircraft type, configuration characteristics, load factors, and routing. Frequency of operation can be ignored, if the routing and local field conditions do not restrict operations. Typically, the smaller communities do not have runway lighting systems, nor instrument landing systems. Although FAA has a

long range development program that may equip many airports with such equipment, the lack of it prevents night time operations and limits bad weather operations. For example, if a current route serves six communities, but takes most of the daylight hours to do so, it is unlikely that additional aircraft service will follow the same route since the circuit cannot be completed within the environmental limitations. New routes must be assumed; most likely these would serve the linkages with the greatest demands. The researcher needs to think through such possible changes and make the assumptions necessary to determine the route structure before loading the aircraft.

Scheduled Commercial Operations

The level of service to smaller communities, as defined by types of aircraft and frequency of service, can be expected to change very slowly under normal economic conditions. In part, this trend reflects the need for smaller air carriers to maximize utilization of their aircraft, as well as their inability to obtain financing for new equipment due largely to very slow growth in passenger emplacements (Parker Associates, 1979). In part this trend also reflects the limits of the aviation facilities, in that some community's facilities cannot handle larger aircraft, either because of the physical condition of the runway, or its length, or both. Unless the physical conditions are expected to change, or rapid economic growth is expected, it is generally assumed that existing types of aircraft will continue in use.

Market structure, **which** includes factors such as travel demand, operational **costs**, and **other items**, has **much** to do with how the **airlines** operate **their** aircraft. Two additional market factors which affect seating capacity in a particular type aircraft, and therefore effect revenue, are aircraft configuration and expected operational load factor. Configuration refers to the way in which passengers and freight are arranged within the aircraft. **Due** to the remoteness of many communities, scheduled air carrier aircraft are typically configured to carry **both**. This **reduces** seating capacity. Configuration data can **usually** be obtained from the airlines.

— **The load factor** reflects the **actual use** of available seating. Ideally, the air carriers would like a **100** percent **load** factor on all flights. However, even during peak periods, the **100** percent level is not **always** reached because the *air* carriers have found they can provide **better service** by adding more **flights** at reduced load factors. Load factors can **still** be quite high. Smaller airlines operating smaller aircraft are more **likely** to operate at 90 to **100** percent of capacity since they need to maximize utilization. *Larger* air carriers are likely to plan operations using load factors between 70 and 90 percent, and may operate a specific route at a **level** as **low** as 50 percent in order to stay **in** a particular market.

Generally, **load** factor data **is difficult to obtain** because **its** an indicator **of** market success. Load factors **can be** inferred from historic data, however, by dividing **total** annual **emplaned** passengers for **commercial** airlines by the **total number of commercial seats available**. This **latter** number is estimated from **the annual number** of flights by type of aircraft and the typical configuration of **each** type aircraft. Unless market conditions change, it is generally assumed **load** factors are rising to some predetermined point, **at which** time additional flights are added **to** the schedule. **Since load** factors **less than 100** percent offer the airline greater **flexibility, it is** assumed **in** this methodology **that, during peak conditions, commercial aircraft load factors will be in the range of 85 to 95** percent.

To calculate the **number** of commercial aircraft **flights, total travel** demand, expressed as emplacements, is divided **by the** average number of seats per aircraft, as determined by applying **the** configuration **and load** factor components. However, in the situation **for** which this methodology was prepared, OCS activities in the **St. George and Navarin Basins will** add petroleum employment **air travel** demands to the **normal** commercial demands of the resident population. Depending upon how these additional demands **are** met, the above calculation might **be** modified. **If** the researcher assumes these added air **travel** demands **will be** accommodated **totally on** chartered flights, **the OCS travel** demands **for each lease** offering can be converted to charter flights using **the** same approach

described above. **If** the researcher assumes these demands will be accommodated on scheduled commercial flights, these demands must be added **to those of** the resident population before computing the number **of** commercial **flights**.

The procedure **to** develop **OCS** worker emplacements is described in **detail in a following** section **of** this report. That procedure must be followed for each **lease** sale scenario; that is, two sets **of OCS** worker emplacement data need be calculated. **It should be** noted that the **OCS** emplacements are calculated **as** trips between the **lease** sale area and general residence location (i.e. one-way **trips**). These trips must be distributed and **assigned to** specific routes, and, therefore, specific airports. **All** these **OCS** trips constitute emplacements at each airport they pass through and these **must** be doubled to reflect the two directional flow (**i.e.** from residence location **to the lease** sale area).

Other Operations

Once total commercial aircraft operations are determined, other types of aircraft operations can be inferred. Historic aircraft operations data should provide the basis for determining a relationship between scheduled commercial operations and those pertaining to charter or contract operations, general aviation, or military (if significant). The historic operational relationships, together with any adjustment factors used to account for deviations from historic trends, are applied

to the total scheduled commercial operations developed above. The results, when added to the scheduled commercial operations, should provide an estimate of total aircraft operations.

Depending upon how explained passenger data was generated, it may be necessary to make seasonal and other adjustments to the operational data to get a true picture of the busier periods at a particular facility. Typically, seasonal peaks in air travel occur during the summer months between May and September, with late June and early July being the busiest four-week period. This is subject to some variation depending on the cause for such peaking. The typical situation throughout Alaska consists of tourist travel and construction activities, however, the change of fishing seasons in the Aleutians may also create significant peak demand periods. The indicator of peak demand used in this methodology is peak daily operations. Peak daily operations are determined as a ratio of average daily operations. Typically this ratio varies from about 1.5 to 2.0. Some sense of the correct ratio can be gleaned from historic data.

The last step in the process is to determine impacts. One of the more common measures of potential impact is a comparative analysis of peak demands and capacity limitations at a facility. A capacity estimate can be made for each of the major features of an airport: runway capacity, air terminal capacity, etc. In general, each of these capacities is a

function of many variables and **the** measurement of most of these beyond the **scope** of this type analysis. Consequently, a surrogate must be **found**. **For** this analysis methodology, runway capacity was chosen. Runway capacity also is a function of many variables that are beyond the scope of this analysis, however, some standard estimates have been prepared for certain runway configurations by ignoring issues like air traffic control, aircraft mix, and others. At smaller airports with **low** traffic volumes disregarding these variables **should** have little consequence. At **the larger** airports such as Anchorage or Fairbanks, which are operating under direct air traffic control, a more sophisticated approach must be taken. The capacity estimates suggested **to** be used in this methodology come from the classic airport planning text "Planning and Design of Airports", by the late Robert **Horonjeff**. (McGraw-Hill Series in Transportation - **1975**). These "crude" estimates, however, are sufficient for the **small** communities **in** this analysts:

OCS RELATED TRANSPORTATION DEMANDS

The OCS work force generates additional **emplaned** passenger **travel** demands at facilities they pass through between their home and work locations. Although some OCS work force **travel** demands are handled by contract or charter air carriers, the majority of travel is done on scheduled commercial air carriers. Within the schema of this methodology, these travel demands are distributed to airport **facilities**

along the principal travel routes and subsequently converted to aircraft flights. The added operations and passengers at each affected airport can then be evaluated for their influence on reducing available airfield capacity. The discussion that follows details this process including the distribution of OCS related operations to affected airports. The analysis of impacts is the same as described earlier.

The beginning point in developing OCS work force travel demands is the OCS Petroleum Employment Model used by MMS. The model breaks OCS employment into 21 major tasks and some tasks are further refined to show transportation support employment. For each major task, estimates are made (by MMS) of crew size, rotation factor, and task duration, among other factors. The percentage of out-of-state commuters and distribution of in-state commuters is also included as input to the model. Output from the model includes average annual employment by task, as well as a summary of jobs by place of permanent residence.

The employment model tasks can be identified as onshore or offshore activities. This distinction is useful for determining offshore travel requirements, therefore, this methodology organizes the tasks into these two categories. The first step involves converting the average annual employment output by the model to peak month employment and distributing these in accordance with the residence rules of the model. The model's inherent assumptions pertaining to task duration are used to develop

peak month employment. To do this, total annual employment is divided by expected task duration (instead of dividing by 12 months per year for average monthly employment). Multiplying average peak month employment by the model's percentage of out-of-state commuters gives peak month employment from outside Alaska. The remaining number of peak month employment is then distributed on the basis of the model's assumptions pertaining to employment distribution within the State. The result of these different distributions for each task is peak month employment by place of permanent residence.

Using rotation factors and assumptions about actual time onsite and offsite, a peak month trip factor must be developed for each model task. The trip factor is defined as the ratio of 30.4167 days per month (based on 365 days per 12 months) and the sum of number of days offsite plus number of days onsite. This factor attempts to identify the number of trips made during the peak month.

$$\text{Trip Factor} = \frac{30.4167 \text{ days per month}}{\text{number of days offsite} + \text{number of days onsite}}$$

The peak month employment developed earlier for each major region of Alaska and Outside is multiplied by the trip factor. The result for each task/sub task is a distribution of peak month air travel demands, by origin/destination, by year. The term "origin/destination" is used

here **to refer** to the location where **an OCS worker** originates and **ends** each rotation to the **job site** (i.e. residence **location**).

In the next step, **all** the onshore **tasks** are **summed** and the offshore tasks are **summed** to get **total** offshore and onshore **travel** demands. The **total** offshore **travel demand** represents the **number of round trips** to be **served by** helicopter. **In the last step**, both **total** onshore and **total** offshore **trips** are then **summed** to arrive at **total OCS** employment air **travel** demand.

Based on the routing selected for OCS trip making, as suggested by the **petroleum development** scenarios and the **origin/destinations** used to distribute **trips**, the **next step is to sum** the **trips** flowing to and through each of **the facilities** along-the **route**. As mentioned above, offshore helicopter **trips to a local community or to** the service base are determined from **the total** offshore **travel** demand. **If activities are** widely dispersed **around** the periphery of the **lease** offering area it may **be** necessary to break out these demands **by** locality and treat **each** separately.

For simplicity, the **trips should be summed** going in one **direction**, for example from the **lease area** to permanent residence. **Trips would be** summed first for the **service base or bases**, then for the next **major hub** enroute, the second **major hub** enroute, and so **forth** until all

destinations are accounted for. The resultant number of trip demands for each route into each facility must then be converted **to** aircraft operations. The requirements for this conversion were discussed in the previous section of this chapter treating non-OCS related **travel** demands. Total trip demands along each route are divided by assumed aircraft passenger capacity taking into account aircraft configuration and expected load factor, also discussed previously.

In the case **where** charter aircraft are used exclusively, each resultant aircraft requirement represents both a landing and **a** takeoff (since workers are traveling in each direction), therefore, **to** obtain a **total** charter operations estimate, the requirements must **be** doubled. This is done for **all OCS** routes into an airport. **Total OCS** charter operations are assumed to represent a portion of **total** air carrier operations at each affected airport. The **OCS** Case operations are then added to **those** developed for the Base Case (non-OCS related operations) to produce a new estimate of total air carrier operations. From this point, the evaluation of **local** facility impacts is as discussed earlier under the section **on** non-OCS related transportation demands.

REFERENCES

- Alaska Consultants, Inc., 1976.** Marine Service Bases for Offshore Oil Development. Prepared for **Alaska** Department of Community and Regional Affairs, Division of Community Planning. Anchorage, Alaska. 87 pp.
- _____, **1981a.** St. George Basin Petroleum Development Scenarios **Local** Socioeconomic Systems Analysis, Technical Report No. 59. Prepared for the Bureau of Land Management, **Alaska** Outer Continental Shelf Office, as part of the **Alaska** OCS Socioeconomic Studies Program, Anchorage, Alaska. 355 pp. with 1 appendix.
- _____, **1981b.** Baseline Socioeconomic Conditions, North Aleutian Shelf and **Navarin** Basins Socioeconomic Systems, Draft Technical Memorandum. Prepared for Bureau of Land Management, Alaska Outer Continental Shelf Office, as part of the Alaska OCS Socioeconomic Studies Program, Anchorage, Alaska. 227 pp.
- Alaska Consultants, Inc. and PRC Harris, Inc., 1981.** **Southcentral** Region of Alaska Deep-Draft Navigation Study. Prepared for the U.S. Army Engineer District, Alaska. Anchorage, Alaska. 130 pp. with Appendices A - J.
- Dames & Moore, **1980a.** Norton Basin OCS Lease Sale No. 57 Petroleum Development Scenarios, Technical Report No. 49. Prepared for **Bureau of** Land Management, Alaska Outer Continental Shelf Office, as part of the **Alaska** OCS Socioeconomic Studies Program, Anchorage, Alaska. 199 pp. with 5 appendices.
- _____, **1980b.** Offshore Runway Extension at **Unalaska** Airport, **Alaska**. Prepared for the Alaska Department of Transportation and **Public** Facilities, Division of Aviation Design and Construction. Anchorage, Alaska.
- Dames & Moore et al., 1980.** St. George Basin Petroleum Technology Assessment, Technical Report No. 56. Prepared for Bureau of Land Management, **Alaska** Outer Continental Shelf Office, as part of the **Alaska** OCS Socioeconomic Studies Program, Anchorage, Alaska. 193 pp. with 2 appendices.
- Dames & Moore et al., **1982.** **Navarin** Basin Petroleum Technology Assessment, Technical Report No. 83. Prepared for Bureau of Land Management, Alaska Outer Continental Shelf Office as part of the Alaska OCS Socioeconomic Studies Program. 110 pp. with appendices.

- Dames & Moore and Harrison, G.S., 1982. Bering Sea Cumulative Economic OCS Petroleum Development (also titled: An Economic Analysis of Concurrent Development of Outer Continental Shelf Oil and Gas Leases in the Bering Sea), Technical Report No. 80.** Prepared for Bureau of Land Management, Alaska Outer Continental Shelf Office, as part of the Alaska OCS Socioeconomic Studies Program. Anchorage, Alaska. 72 pp.
- DMJM Forssen, in association with Tetra Tech, 1980. Aleutian and Southwest Alaska Coastal Ferry Study.** Prepared for State of Alaska Department of Transportation and Public Facilities. Anchorage, Alaska. Numbered by section with appendices.
- Earl R. Combs, Inc., 1981. St. George Basin Petroleum Development Scenarios Commercial Fishing Industry Analysis, Technical Report No. 60.** Prepared for Bureau of Land Management, Alaska Outer Continental Shelf Office, as part of the Alaska OCS Socioeconomic Studies Program. Mercer Island, Washington. 153 pp. with a technical appendix.
- Engineering Computer Optecnomics, Inc., 1977. An Assessment of Marine Transportation Costs Related to Potential Port Sites in Alaska, Commission Study 25.** Prepared for Federal-State Land Use Planning Commission for Alaska. Anchorage, Alaska. 37 pp. plus 29 appendices.
- ERE Systems, Ltd., 1982. Western Alaska Transportation Systems Analysis, Technical Report No. 66.** Prepared for Peat, Marwick, Mitchell, & Co. and Bureau of Land Management, Alaska Outer Continental Shelf Office, as part of the Alaska OCS Socioeconomic Studies Program, Anchorage, Alaska. 132 pp. plus appendix.
- Global Marine Engineering Company, 1978. A Preliminary Feasibility Study of A Tanker Transportation System Serving the Northwest Coast of Alaska, Final Report - Executive Summary (Part 1 of 3).** Prepared for the U.S. Department of Commerce, Maritime Administration, Office of Commercial Development. Newport Beach, California. pp. unk.
- Horonjeff, R., 1975. Planning and Design of Airports.** McGraw-Hill Book Company, New York, New York. 461 pp.
- Kramer, L. S., Clark, V. C., and Canelos, G. J., 1978. Planning For Offshore Oil Development, Gulf of Alaska OCS Handbook.** Alaska Department of Community and Regional Affairs, Division of Community Planning. Juneau, Alaska. 257 pp.

Lewis, S., **1981**. Telephone conversation between John **Tremont**, Minerals Management Service, Alaska Outer Continental Shelf Region, and Steve Lewis, Atlantic Richfield Company, discussing drilling mud and cement requirements for exploration and development wells. July **6**. Anchorage, Alaska.

Louis **Berger** and Associates, Inc., **1981**. Technical Memorandum **SI-1**, A Description of the Population of Two Selected Regions of Alaska, NANA Region **Aleutian/Pribilof**, Prepared for Bureau of Land Management. Anchorage, Alaska pp **unk**.

_____, **1983**. **Navarin** Basin (Sale 83) Transportation Systems Impact **Analysis**, Technical Report No. 84. Prepared for Minerals Management Service, Alaska Outer Continental **Shelf** Region, as part of its **Social** and Economic Studies Program. Anchorage, Alaska. **227 pp.**

Louis **Berger** and Associates, Inc., in association with **Phillio** -Engineering and Architectural **Service, Inc., 1979**. Western and Arctic **Alaska** Transportation Study. Phase I, Volume I - V; Phase **II, Volume I - IV**; Phase **III, Volume I - VI**. Alaska Department of Transportation and Public Facilities. Fairbanks, Alaska.

Military **Sealift** Command, Department of the Navy, 1982. **Annual** Alaska Resupply Program, Project COOL BARGE, Request For Proposal **No. N0003382R1003**. Washington, D.C. 24 pp. plus 6 data appendices.

New England River Basins Commission, 1976. **Factbook: Onshore Facilities** Related to Offshore Oil and Gas Development. Report of the **project** "Development and Application of a Methodology for Siting Onshore Facilities Associated with OCS Development"; prepared as part of the **U.S.** Department of the Interior, Geological Survey, Resource and Land Investigations (**RALI**) Program. The Commission. Boston, Massachusetts.

Northern Resource Management, 1980. Monitoring Oil Exploration Activities in the Lower Cook Inlet, Technical Report No. **55**. Prepared for the Bureau of Land Management, Alaska Outer Continental Shelf Office. Anchorage, Alaska. 206 pp. plus appendix.

Payne, **J.T.** and **Braund, S.R., 1981**. North Aleutian Shelf Basin **Sociocultural** Systems Analysis. Prepared for the Bureau of Land Management, Alaska Outer Continental Shelf Office, as part of the Alaska OCS Socioeconomic Studies Program. Anchorage, Alaska. 376 pp "

Parker Associates, 1979. Air Service to Rural Alaska: A Study in

- Inadequacy.** Prepared under contract with the Division of Legislative Finance for the Alaska House Finance Committee. Juneau, Alaska. 219 pp.
- Peat, Marwick, Mitchell & Co., 1980. Bering-Norton Petroleum Development Scenarios Transportation Systems Analysis, Technical Report No. 52. Prepared for Bureau of Land Management, Alaska Outer Continental Shelf Office as Part of the Alaska OCS Socioeconomic Studies Program, Anchorage, Alaska. 337 pp. plus 2 appendices.
- Peat, Marwick, Mitchell & Co. and ERE Systems, Ltd., 1981. St. George Basin Transportation Systems Impact Analysis. Technical Report No. 58. Prepared for the Bureau of Land Management, Alaska Outer Continental Shelf Office as part of the Alaska OCS Socioeconomic Studies Program. Anchorage, Alaska. 337 pp. plus 2 appendices.
- Quinn, Alonzo De F., 1961. Design and Construction of Ports and Marine Structures. McGraw-Hill Book Company, New York, New York. 521 pp.
- Springer, G.C., 1983. Development Strategy for The Navarin Basin. U.S. Department of the Interior, Minerals Management Service, Alaska Outer Continental Shelf Region, Reference Paper 83-2. Anchorage, Alaska. 15 pp.
- State of Alaska, Department of Commerce and Economic Development, 1979. Basic Economic Statistics of Alaska Census Divisions. Juneau, Alaska. 127 pp..
- State of Alaska, Department of Health and Social Services. Annual . . . Alaska Vital Statistics Annual Report, for the years 1979-1981. Juneau, Alaska. pp. variable.
- Terry, J.M., Stoles, R.G., and Larson, D.M., 1980. Western Alaska and Bering-Norton Petroleum Development. Scenarios Commercial Fishing Industry Analysis, Technical Report No. 51. Prepared by the University of Alaska, Alaska Sea Grant Program for the Bureau of Land Management, Alaska Outer Continental Shelf Office, as part of the Alaska OCS Socioeconomic Studies Program. Fairbanks, Alaska. 737 pp.
- Tremont, J., 1983. Personal conversation between R.W. Schmidt, ERE Systems, Ltd., and John Tremont, Minerals Management Service, Alaska Outer Continental Shelf Region, regarding assumptions to be used in dealing with concurrent development of four lease sales in the Bering Sea. September 1983.
- U.S. Army Corps of Engineers, Annual. Waterborne Commerce of the United States. Part 4. Waterways and Harbors - Pacific Coast, Alaska,

and Hawaii. Vicksburg, Miss. 120 pp.

- U.S. Coast Guard, 1980. Summary of Unalaska/Dutch Harbor Planning Conference, 17 April 1980. Memorandum prepared by Seventeenth Coast Guard District. Juneau, Alaska. 9 pp. with 3 enclosures.
- U.S. Department of Commerce, National Oceanic and Atmospheric Administration, 1983. United States Coast Pilot, Pacific and Arctic Coast Alaska, Cape Spencer to Beaufort Sea. Tenth Edition. Washington, D.C.
- U.S. Department of Interior, Bureau of Land Management, 1982. Final Environmental Impact Statement, Proposed Outer Continental Shelf Oil and Gas Lease Sale, Norton Sound. Anchorage, Alaska. 332 pp. plus tables, figures, bibliography, and Appendices A - L.
- U.S. Department of the Interior, Minerals Management Service, 1982. Final Environmental Impact Statement, Proposed Outer Continental Shelf Oil and Gas Lease Sale, St. George Basin. Anchorage, Alaska. pp. plus tables, figures, bibliography, and Appendices A - K. Reference includes a separate supplemental document of 38 pp. with Appendices A - C.
- U.S. Department of Transportation, Federal Aviation Administration, Alaska Region, 1981. Ten Year Plan FY 1983 - FY 1992. Anchorage, Alaska.
- U.S. Department of Transportation, Federal Aviation Administration and Civil Aeronautics Board, Annual. Airport Activity Statistics of Certified Route Air Carriers. Annual issues since- 1976. Washington, D.C.
- University of Alaska, Arctic Environmental Information and Data Center, 1978. St. George. A community profile pamphlet prepared for the Alaska Department of Community and Regional Affairs. Anchorage, Alaska.
- University of Alaska, Institute for Social and Economic Research, 1980. St. George Basin Petroleum Development Scenarios Economic Analysis. Draft Report. Prepared for the Bureau of Land Management, Alaska Outer Continental Shelf Office, as part of the Alaska OCS Socioeconomic Studies Program. Anchorage, Alaska. 250 pp.
- University of Alaska, Institute for Social and Economic Research, 1981. Base Case Assumptions for North Aleutian Shelf Statewide and Regional Economic Systems Impact Analysis (OCS Sale No. 75). Draft Report. Prepared for the Bureau of Land Management, Alaska Outer Continental Shelf Office, as part of the Alaska OCS Socioeconomic Studies Program. Anchorage, Alaska. 67 pp.